

# Product data sheet

## SIGA-Fentrim® grommet white

**Updated on:** 15.02.2023

**Distributor:** SIGA

**Application:** Self-adhesive sleeve for sealing of penetrations through the airtight layer, e.g. with vapour control layers, wood-based panels, etc.

**Installation instruction:** see manual

**Construction:** flexible EPDM grommet with special film/fleece collar (that can be plastered over), coated with SIGA high performance adhesive

**Packaging unit:** Ø 8-12mm / 15-22mm / 22-25mm      10 grommets / box  
 Ø 100-110mm      4 grommets / box

Characteristics:

		Standards	Units	Values
<b>Dimensions</b>	length x with (product size)		mm	150 x 150 (<Ø 25mm) 320 x 320 (>Ø 100mm)
<b>Temperature resistance</b>			°C	-40 °C to +100 °C
<b>Processing temperature</b>			°C	from -10 °C
<b>Tensile properties collar Maximum tensile strength</b>	lengthwise crosswise	EN 12311-1	N/50mm	220 140
<b>Tensile properties collar Elongation at maximum tensile strength</b>	lengthwise crosswise	EN 12311-1	%	70 80
<b>Ageing resistance</b>	high permanent adhesive strength and flexibility, can reliably and durably absorb structural movements			
<b>Emissions</b>	Free of halogens and domestic toxins			
<b>Suitability for storage</b>	Unlimited, in cool and dry conditions			
<b>Colour</b>	white			
<b>Requirements for reliable bonding</b>	The substrate must be dry, uninterrupted, even, capable to bear loads, free of dust and grease and must not repel adhesives. Clean substrate before bonding and perform adhesion test on site.			