

VisqueenPro Double Sided Jointing Tape, 50mm x 10m

Features and benefits

- Third party certification - part of a dpm/ gas protection BBA approved jointing system
- Gas resistant - provides excellent resistance to harmful bulk gases ingress and moisture ingress
- Excellent adhesion - to gas and damp proof membranes

Product description

VisqueenPro Double Sided Jointing Tape is a double sided butyl based compound with an oversize quick release film. It is available in roll format 50mm x 10m.

To complete the joint use the Visqueen Gas Resistant Foil Tape for gas applications and use the Visqueen Pro Single Sided Tape for damp applications.

Approvals and standards

- Third party accreditation - BBA certification
- Conforms to the specification requirements of BS 8485:2015 + A1:2019
- Quality Management System ISO 9001:2015
- Occupational Health and Safety System ISO 18001:2007
- Environmental Management System ISO 14001:2015


Usage

VisqueenPro Double Sided Jointing Tape is used to bond membranes (gas or damp) together along the appropriate sheet lap ends. It can also be used for patch work where the membrane is punctured, creating airtight seals around pipe penetrations and bonding the floor membrane to the damp proof course at the horizontal plane.

To complete the joint use the Visqueen Gas Resistant Foil Tape for gas applications or use the Visqueen Pro Single Sided Tape for damp proof membranes.

System components

Find your local stockist



VisqueenPro Double Sided Jointing Tape, 50mm x 10m

Storage and handling

Store in warm, dry and clean environment in its current packaging. The tape should not be exposed to long periods of ultraviolet light. In very cold weather, prior to use ensure that the material is stored in warm conditions above 5°C.

Preparation

Ensure all surfaces are clean and dry. The membrane joint surfaces should be dry and free from contamination such as dust or sand. Ensure the surface and working area is not water logged. Avoid areas of unsupported jointing.

Installation

Apply VisqueenPro Double Sided Jointing Tape to the lap area of the laid sheet starting approximately 50mm from the membrane edge. Apply pressure to the tape to ensure the tape has adhered to the membrane. Remove quick release paper from the tape and overlap the adjoining membrane by minimum 150mm. For Visqueen damp proof membranes and gas protection membranes lap joints should then be sealed using the appropriate Visqueen lap tape. Once the tape is applied, the completed lap should be well rolled with firm pressure to ensure a complete seal joint has occurred, and continuity with the adjacent sheet has been achieved.

If the membrane is punctured or perforated a patch of the same material should be lapped at least 150mm beyond the limits of the puncture and bonded with VisqueenPro Double Sided Jointing Tape and sealed with the appropriate lap tape.

Airtight seals should be formed around all service entry points. Visqueen Preformed Top Hat Units should be used for sealing service entry pipes. The base of the top hat and the upstand should be bonded using Visqueen Pro Double Sided Jointing Tape and sealed with Visqueen Foil Lap Tape. The upstand should be secured with the supplied jubilee clip.

Usable temperature range

It is recommended that VisqueenPro Double Sided Jointing Tape and other system components should be used above 5°C.

Additional information

VisqueenPro Double Sided Jointing Tape, 50mm x 10m

Property	Result
Width	50mm
Length	10m
Colour	Blue
Adhesive type	Butyl
Dynamic Shear Adhesion	14 N/cm ²
Dynamic Tensile Adhesion	18 N/cm ²
180° Peel Adhesion	11 N/cm ²
Moisture Vapour Transmission Rate	0.24 g/m ² /d
Service Temperature Range	-40 to 90°C
Application temperature	>5°C

Health and safety information

Please refer to material safety datasheet.

VisqueenPro Double Sided Jointing Tape, 50mm x 10m

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing



Gas Protection



Damp Proof Membrane



Tapes



Damp Proof Course



Stormwater



Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen PI designs and special projects

From initial design to the completed project, Visqueen are with you every step of the way. Whether it be hazardous ground gas protection and/or below ground waterproofing protection employing barrier, structurally integral or drained systems, Visqueen can offer professional indemnity (PI) insurance for bespoke Visqueen design solutions.

Visqueen Technical Support Managers work with all stakeholders to provide cost effective Visqueen solutions offering complete peace of mind throughout the construction phase and beyond.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive three day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.