

## Safe-R

Superior Performance  
Phenolic Insulation

## SR/PR

Insulation for  
Pitched Roof at Rafter Level

The pitched roof insulation shall be Xtratherm Safe-R SR/PR \_\_ \_\_mm manufactured to EN 13166 by Xtratherm, comprising a rigid Phenolic core between low emissivity foil facings. The SR/PR \_\_mm with Agrément declared Lambda value as low as 0.020W/mK to achieve a U value of \_\_W/m<sup>2</sup>K for the roof element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause P10 140, K11 695, K11 55, K10 245

### Insulation

Phenolic Rigid Foam

### Standard

BS EN 13166

### Certification

BBA Certification No. 10/4803. Issue date: 14 December 2010  
BS EN ISO 9001 Quality Management System  
BS EN ISO 14001 Environmental Management System

### Manufacturer

#### Xtratherm UK Limited

Holmewood Industrial Park, Holmewood  
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

[info@xtratherm.com](mailto:info@xtratherm.com)

[www.xtratherm.com](http://www.xtratherm.com)

### Face size

2400 x 1200 mm

### Edge profile

Straight Edge

### Thickness

25mm / 50mm / 60mm / 75mm / 80mm /  
100mm / 120mm

### Product reference

Xtratherm Safe-R SR/PR  
Pitched Roof Insulation

Other sizes available dependent on quantity & lead time.