

XtroLiner

Superior Performance PIR Insulation

XO/PR

Insulation for
Pitched Roof at Rafter Level

The pitched roof insulation shall be Xtratherm XtroLiner XO/PR manufactured to EN 13165 by Xtratherm, comprising a rigid modified Polyisocyanurate (PIR) core with textured low emissivity foil facings. The XO/PR __ _mm with a Agrément declared Lambda value of 0.021 W/mK to achieve a U value of __ _W/m²K for the roof element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause P10 140, K11 695, K11 55

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer**Xtratherm UK Limited**

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.comwww.xtratherm.com**Xtratherm Limited**

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.iewww.xtratherm.ie**Face size**

2400 x 1200 mm

Edge profile

Straight Edge

Thickness

50mm / 60mm / 75mm / 80mm /
100mm / 120mm

Product reference

Xtratherm XtroLiner XO/PR
Pitched Roof Insulation

Other sizes available dependent on quantity & lead time.