RAVATHERM[™] XPS X 300 SL



Technical data sheet

Properties	Value				Unit	Unit		Standard		CE Code	
Thermal Conductivity Declared	0.030		< 60mr	n	W/m.K		EN 13164			λD	
	0.031		≥ 60mr	n	W/m.K						
Compressive stress or compressive strength@ 10% deformation	300				kPa		EN 826		CS	CS(10\Y)	
Compressive Creep max after 50 years < 2% deformation under stress σC	130				kPa		EN 1606		CC(2/	CC(2/1.5/50)σ	
Water vapour diffusion resistance factor $\boldsymbol{\mu}$ (tabulated value)	100				-		E	EN 12086		MU	
Long term water absorption by total immersion	< 0.7				%		E	EN 12087		/L(T)	
Water pick-up by diffusion			50 < 80n	nm	%		EN 12088		W	/D(V)	
			≥ 80mr	n							
Water pick up after Freeze Thaw	< 1				%		E	EN 12091 FT0		TCD	
Dimensional stability under specified temperature (70°C) and humidity conditions (90%rh)	< 5				%		EN 1604		DS(70,90)		
Coefficient of linear thermal expansion (typical value)	0.07				mm/(m.K)		-		-		
Fire Performance	E				Euroclass		EN 13501-1				
Temperature limits	-50/+75				°C		-				
Thickness tolerances	1				Class		EN 823		т		
Dimensions Width	600				mm		EN 822				
Length	1250				mm		EN 822				
Edge Profile	Ship lap										
Surface finish	Skin										
Thermal resistance ¹											
Thickness(mm)	50	80	100	120	130	1	140	160	180	200	
R _d m².K/W	1.65	2.60	3.20	3.85	6 4.20	4	1.50	5.15	5.80	6.45	
DESIGNATION CODE: XPS-EN 13164-T1-CS(10\Y)300-CC(2/1.5/50)130-DS(70,90)-WL(T)0.7- WD(V)1,2,3 ⁽¹⁾ -FTCD1											

1) Thickness dependant

1 N/mm² = 10³ kPa = 1MPa

Material shall be stored inside in original packaging, away from direct sun light or heat sources

Note: The information and data contained in this technical data sheet do not represent exact sales specifications. The features of the products mentioned may vary. The information contained in this document has been provided in good faith, however it does not imply any liability. guarantee or assurance of product performance. It is the purchaser's responsibility to determine whether these products are suitable for the application desired and to ensure that the site of work and method of application conform with current legislation. No license is hereby granted for the use of patents or other industrial or intellectual property rights. If products are purchased, we advise following the most up-to-date suggestions and recommendations.

