

SC9830 CHARGING & CONNECTIVITY STATION



STANDARD SPECIFICATIONS

STRUCTURE

Galvanized Steel 2mm / PVC plastic
Performance coating.

DIMENSIONS

71 x 63 x 110 in / 180 x 160 x 280 cm

UNIT PERFORMANCE

USB Charging Ports: 2, 5V/2.1A: Up to 4

Inductive Charging Pad: Up to 2

Wi-Fi Router – 4G LTE 60ft / 18.2m

10W LED array – 2.5 ft-candles | L70 rating: 75,000 hr

Operating Ambient Temperature:

-25°C – 65°C | -13°F – 149°F

30hrs+ Autonomous Operation – Automatic On/Off

Adjustable Solar Panel Optional

POWER COLLECTION

80W-120W Monocrystalline Solar Panel

22.8% Efficiency

MOUNTING

Anchor Mount

POWER STORAGE

55Ah – 110Ah High Performance Lithium Batteries-
2,000 Cycle Rating

OPTIONS

Output; Light Temperature; Coating Color

WARRANTY

Accompanied by 3 year limited warranty.

For ordering or questions please contact SELS USA at
704-495-3535 or CustomerService@SELSLED.com
4747 Kester Mill Rd, Winston-Salem, NC 27103



Patent Pending