

# SC9840 CHARGING & CONNECTIVITY STATION

## STANDARD SPECIFICATIONS

---



### STRUCTURE

Stainless Steel 2mm / PVC plastic  
Performance coating.

### DIMENSIONS

30 x 110 in / 680 x 280 cm

### UNIT PERFORMANCE

USB Charging Ports: 2, 5V/2.1A: Up to 6

Inductive Charging Pad: Up to 4

Wi-Fi Router – 4G LTE 60ft / 18.2m

10W LED array – 2.5 ft-candles | L70 rating: 75,000 hr

### Operating Ambient Temperature:

-25°C – 65°C | -13°F – 149°F

30hrs+ Autonomous Operation – Automatic On/Off

Adjustable Solar Panel Optional

### POWER COLLECTION

80W-120W Monocrystalline Solar Panel

22.8% Efficiency

### MOUNTING

Anchor Mount

### POWER STORAGE

55Ah – 110Ah High Performance Lithium Batteries-

2,000 Cycle Rating

### OPTIONS

Output; Light Temperature; Coating Color

### WARRANTY

Accompanied by 5 year limited warranty.

For ordering or questions please contact SELS USA at 704-

495-3535 or [CustomerService@SELSLED.com](mailto:CustomerService@SELSLED.com)

2995 Starlight Dr, Winston-Salem, NC 27107



Patent Pending