



BRAVEPRO



POWERED by HONDA

Bits sold separately

1
PERSON

BRP240HHD

Number of Operators	1 Person
Engine Brand	Honda GX35
Engine Starter	Recoil
Engine Displacement	35 cc
Transmission	Enclosed, Spur Gear, Double Reduction
Rotation Speed	166 RPM (No Load)
Capacity	2" to 8" Diameter
Drive Connection	1" Round
Digging Length w/ Round Bit <i>(Sold Separately)</i>	30" w/o extension
Auger Extension	15" Plain Tube Type
Clutch	All-Metal Automatic-Centrifugal
Max. Drilling Torque	55 ft lbs
Throttle Control	Twist Grip
Operator Handle	Comfort-Zone®
Reduction Ratio	42.5 to 1
Weight (Less Auger)	27 lbs
Consumer Warranty	2 Year Limited
Commercial Warranty	1 Year Limited

BRAVEPRO



POWERED by HONDA

Bits sold separately

2
PERSON

BRP330HHD

Number of Operators	2 Person
Engine Brand	Honda GXV160
Engine Starter	Recoil
Engine Displacement	163 cc
Transmission	Enclosed, Spur Gear, Double Reduction
Rotation Speed	144 RPM (No Load)
Capacity	2" to 18" Diameter
Drive Connection	1-3/8" Hexagon
Digging Length w/ Hexagon Bit <i>(Sold Separately)</i>	36" w/o extension
Auger Extension	15" Plain Tube Type
Clutch	All-Metal Automatic-Centrifugal
Max. Drilling Torque	190 ft lbs
Throttle Control	Twist Grip
Operator Handle	Comfort-Flex®
Reduction Ratio	25 to 1
Weight (Less Auger)	71 lbs
Consumer Warranty	2 Year Limited
Commercial Warranty	1 Year Limited

① Comfort-Zone® Operator Handles
 Comfort-Zone® (BRP240HHD) composite handle design helps maximize operator strength while reducing the effects of kickback and body fatigue. Paired with Twist Grip throttle control for simple operation.

Comfort-Flex® Operator Handles
 Comfort-Flex® (BRP330HHD/BRP343HHD) composite handles flex under load to help absorb vibration and shock. Paired with Twist Grip throttle control for simple operation.

② All Metal Centrifugal Clutch
 Clutch slips on overload or when striking buried objects.

③ Planetary Drive with Solid Cut Steel Gears
 Drive delivers more power for difficult installations and reliable gears mean less maintenance.

④ Auger Bits
 Bits come in multiple diameters to fit your needs from 2" to 18".



Know what's below.
 Call before you dig.



BRAVEPRO

POWERED BY
HONDA



Bits sold separately

2
PERSON

BRP343HHD

Number of Operators	2 Person
Engine Brand	Honda GXV160
Engine Starter	Recoil
Engine Displacement	163 cc
Transmission	Enclosed, Spur Gear, Double Reduction
Rotation Speed	144 RPM (No Load)
Capacity	2" to 18" Diameter
Drive Connection	7/8" Square/Ground Hog® Type
Digging Length w/ Square/Ground Hog Type Bit (Sold Separately)	36" w/o extension
Auger Extension	15" Plain Tube Type
Clutch	All-Metal Automatic-Centrifugal
Max. Drilling Torque	190 ft lbs
Throttle Control	Twist Grip
Operator Handle	Comfort-Flex®
Reduction Ratio	25 to 1
Weight (Less Auger)	71 lbs
Consumer Warranty	2 Year Limited
Commercial Warranty	1 Year Limited

AUGER ACCESSORIES



ITEM #	DIAMETER	LENGTH
Round Bits		
BR10580	2"	30"
BR10581	3"	30"
BR10582	4"	30"
BR10583	6"	30"
BR10584	8"	30"

Hexagon Bits		
BR10586	2"	36"
BR10587	6"	36"
BR10588	8"	36"
BR10590	12"	36"
BR10591	14"	36"
BR10592	16"	36"
BR10593	18"	36"

Square/Ground Hog® Type Bits		
BR10595	4"	36"
BR10596	6"	36"
BR10597	8"	36"
BR10598	10"	36"
BR10599	12"	36"
BR10600	14"	36"
BR10601	16"	36"
BR10602	18"	36"

ITEM #	DESCRIPTION
Bit Extensions	
BR10585	15" Round
BR10594	15" Hexagon
BR10603	15" Square/Ground Hog®

Replacement Auger Blades	
BR10604	4"
BR10605	6"
BR10606	8"
BR10607	10"
BR10608	12"

Screw Bits	
BR10609	Fits BRP240HHD (except 2" and 3" diameter)
BR10611	Fits BRP330HHD & BRP343HHD
BR10611	Fits BRP330HHD

Teeth	
BR10610	Hardfaced Dirt