



X-Maxx (Model 77086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

Bearings & Bushings

5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)
5108A	Ball bearing, black rubber sealed (15x26x5mm) (2)
5107A	Ball bearing, black rubber sealed (17x26x5mm) (2)
5182A	Ball bearing, black rubber sealed (20x27x4mm) (2)
5106	Ball bearing, blue rubber sealed (15x24x5mm) (2)
4611	Ball bearings (5x11x4mm) (2)
5120A	Ball bearings, black rubber sealed (12x18x4mm) (2)
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)

Body & Accessories

7715	Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine screw (2)
7713	Body support, rear/ 3x15mm CS (2)/ 3x15mm flat-head machine (2) (fits X-Maxx®)
7711	Body, X-Maxx® (clear, trimmed, requires painting)/ window masks/ decal sheet
7711A	Body, X-Maxx®, blue (painted, decals applied) (assembled with front & rear body mounts, rear body support, and tailgate protector)
7711G	Body, X-Maxx®, green (painted, decals applied) (assembled with front & rear body mounts, rear body support, and tailgate protector)
7711X	Body, X-Maxx®, ProGraphix® (graphics are printed, requires paint & final color application)/ decal sheet
7711R	Body, X-Maxx®, red (painted, decals applied) (assembled with front & rear body mounts, rear body support, and tailgate protector)
7711T	Body, X-Maxx®, Rock n' Roll (painted, decals applied) (assembled with tailgate protector)
7712	Tailgate protector/ 3x8mm flat-head screw (4)

Bumpers & Skidplates

7733	Bumper mount, front/ bumper support
7734	Bumper mount, rear/ bumper support
7735	Bumper, front
7736	Bumper, rear
7745	Skidplate, center
7744	Skidplate, front (1), rear (1)/ rubber impact cushion (2)

Chassis & Attachments

7719	Battery hold-down (2)/ foam pad (2)
7718	Battery hold-down mounts, left (2)/ right (2)/ 3x18mm CS (4)
7715	Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine screw (2)
7724	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4)
7733	Bumper mount, front/ bumper support
7734	Bumper mount, rear/ bumper support
7735	Bumper, front
7736	Bumper, rear
7722	Chassis
7714X	Chassis top brace
7723	Nerf bars, chassis (2)
7725	Seal kit, receiver box (includes o-ring, seals, and silicone grease)
7745	Skidplate, center
7744	Skidplate, front (1), rear (1)/ rubber impact cushion (2)
7717X	Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2)
7776	Wheelie bar, black (assembled)
7775	Wheels (2) for #7776 wheelie bar)

Cush Drive Components

7794	Cush drive key/ pin/ elastomer damper
7793X	Housing, cush drive (front & rear halves)
6447X	Spur gear, 46-tooth, steel (1.0 metric pitch)
6448X	Spur gear, 50-tooth, steel (1.0 metric pitch)
6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)

Differential Components

7781X	Carrier, differential (aluminum) (requires #7783X spider gear shaft)
7781	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
7782	Gear set, differential (output gears (2)/ spider gears (4)/ 16x23.5x.5mm TW (2))
5041	Grease, premium high performance (20cc)
7780	Housing, differential (front/rear)
5040	Oil, differential (20M weight) (standard)

7790	Pinion gear, differential, 11-tooth (front) (heavy duty) (use with #7792 35-tooth differential ring gear)
7791	Pinion gear, differential, 11-tooth (rear) (heavy duty) (use with #7792 35-tooth differential ring gear)
7792	Ring gear, differential, 35-tooth (heavy duty) (use with #7790, #7791 11-tooth differential pinion gears)
7783	Spider gear shaft (2)/ spacers (4)/ 16x23.5x.5mm TW (2)
7783X	Spider gear shaft (2)/ spacers (4)/16x23.5x.5 stainless washer (2) (for #7781X aluminum differential carrier)

Driveline Components

7752	Carriers, stub axle (left & right)
7794	Cush drive key/ pin/ elastomer damper
7754X	Drive cup (1)/ 3x8mm CS (use only with #7750X driveshaft)
7755	Driveshaft assembly, center, aluminum
7750X	Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1) (replacing #7750 also requires #7751X, #7754X and #7768, #7768R, or #7768G)
5040	Oil, differential (20M weight) (standard)
7751X	Rebuild kit, steel constant-velocity driveshaft (includes pins for 2 driveshaft assemblies (use only with #7750X driveshaft)
7768A	Stub axle, aluminum (black-anodized) (1) (use only with #7750X driveshaft)
7768	Stub axle, aluminum (blue-anodized) (1) (use only with #7750X driveshaft)
7768G	Stub axle, aluminum (green-anodized) (1) (use only with #7750X driveshaft)
7768R	Stub axle, aluminum (red-anodized) (1) (use only with #7750X driveshaft)
7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)

Front Suspension & Steering

7726	Bulkhead tie bar, upper (1)/ lower (2) (steel)
7721	Bulkhead, front (lower)
7720	Bulkhead, front (upper)
7752	Carriers, stub axle (left & right)
7732	Caster blocks (c-hubs), left & right
7716	Mount, tie bar, front (1)/ rear (1)
7747	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
7739	Shock tower, front (left & right halves)
7746	Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
7737	Steering blocks, left & right
7746X	Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo)
7731	Suspension arms, lower (left, front or rear) (1)
7730	Suspension arms, lower (right, front or rear) (1)
7729	Suspension arms, upper (left or right, front or rear) (2)
7743	Suspension pin retainer (4)
7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)
7742	Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)
7741	Suspension pins, 4x85mm (hardened steel) (2)

Hardware

2585	Cylinder head bolts, marine 3x20mm CS (6) (TRX 2.5)
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5, 2.5R, 3.3)
2586	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)
4955	Pins, axle (2.5x12mm) (4)
3234	Screws, 2.5x14mm cap-head machine (hex drive) (6)
2577	Screws, 3x10mm button-head machine (hex drive) (6)
2587	Screws, 3x10mm cap-head machine (6) (no washer)
4859	Screws, 3x10mm flat-head machine (hex drive) (4)
2593	Screws, 3x14mm button-head machine (hex drive) (6)
2579	Screws, 3x15mm button-head machine (hex drive) (6)
3646	Screws, 3x15mm flat-head machine (hex drive) (6)
4857	Screws, 3x20mm countersunk machine (hex drive) (6)
2581	Screws, 3x25mm button-head machine (hex drive) (6)
2575	Screws, 3x6mm button-head machine (hex drive) (6)
2576	Screws, 3x8mm button-head machine (hex drive) (6)
2535	Screws, 4x10mm countersunk machine (hex drive) (6)
3937	Screws, 4x12mm button-head machine (hex drive) (6)

Page 2 X-Maxx: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

- 3938 Screws, 4x14mm button-head machine (hex drive) (6)
- 2594 Screws, 4x15mm button-head machine (hex drive) (6)
- 2546 Screws, 4x15mm countersunk machine (hex drive) (6)
- 3933 Screws, 4x16mm button-head machine (hex drive) (6)
- 2597 Screws, 4x22mm button-head machine (hex drive) (6)
- 2596 Screws, 4x25mm button-head machine (hex drive) (6)
- 2598X Screws, 4x30mm button-head machine (hex drive) (6)
- 2595 Screws, 4x35mm button-head machine (hex drive) (6)
- 2743 Set (grub) screws, 3mm hardened (12)
- 3642X Shoulder screws, Ultra Shocks (3x12 hex drive) (6)

LED Lights

- 7885 LED light kit, complete (includes #6590 high-voltage power amplifier)

Motors & Electronics

- 7749 Adapter, standard servo (adapts standard servo to fit in X-Maxx®)
- 3475 Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)
- 7787 Covers, gear (3)
- 3474 Dual cooling fan kit (with shroud), Velineon® 1200XL motor
- 2087 Gear set (for 2085 servo)
- 2087X Gear set, metal (for 2085 & 2085X servos)
- 3362 Heat sink, Velineon® 1600XL
- 7760 Motor mounts (front and rear)/ pins (2)
- 3491 Motor, Velineon® 1200XL, brushless
- 2086 Servo case/gaskets (for 2085 servo)
- 2085 Servo, digital high-torque (ball bearing), waterproof (X-Maxx® mount)
- 2085X Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link
- 3496 Velineon® VXL-8s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)
- 7759 Washers, motor mount, aluminum (blue-anodized) (4)/ 4x18mm BCS (4)
- 7759G Washers, motor mount, aluminum (green-anodized) (4)/ 4x18mm BCS (4)
- 7759R Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm BCS (4)

Radio System, Batteries & Chargers

- 2854X 10000mAh 7.4v 2-Cell 25C LiPo Battery
- 2872X 5000mAh 11.1v 3-Cell 25C LiPo Battery
- 2888X 5000mAh 14.8v 4-Cell 25C LiPo Battery
- 2889X 5000mAh 14.8v 4-Cell 25C LiPo Battery
- 2857X 6400mAh 11.1v 3-Cell 25C LiPo Battery
- 2890X 6700mAh 14.8v 4-Cell 25C LiPo Battery
- 2878X 8400mAh 11.1v 3-Cell 25C LiPo Battery
- 2938X Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries to separate balance ports)
- 2943 Battery charge indicators (green (4), blue (4), grey (4))
- 6548 Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)
- 2914 Battery, Power Cell AA Alkaline (4)
- 2993 Battery/charger completer pack (includes #2971 iD® charger (1), #2890X 6700mAh 14.8V 4-cell 25C LiPo battery (2))
- 2990 Battery/charger completer pack (includes #2972 Dual iD® charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))
- 2972 Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification
- 2973 Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto Battery Identification
- 2971 Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification
- 2970 Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification
- 6525 Communication link, telemetry expander
- 2087 Gear set (for 2085 servo)
- 2087X Gear set, metal (for 2085 & 2085X servos)
- 2968X LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)
- 2968 LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)
- 6533 Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
- 6552 Seal kit, expander box (includes o-ring, seals, and silicone grease)
- 6526 Sensor, auto-detectable, temperature
- 6527 Sensor, auto-detectable, voltage
- 6531 Sensor, temperature & voltage (fits X-Maxx®)
- 6521 Sensor, temperature and voltage (long)
- 2086 Servo case/gaskets (for 2085 servo)
- 2085 Servo, digital high-torque (ball bearing), waterproof (X-Maxx® mount)
- 2085X Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link

- 6553X Telemetry expander 2.0 and GPS module 2.0, TQi radio system
- 6550X Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module)
- 6550 Telemetry expander, TQi radio system
- 6551X Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander)
- 6509R TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver)
- 6507R TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)
- 6528 Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only)
- 6529 Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only)
- 6530 Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only)
- 6511 Traxxas Link™ Wireless Module

Ready-To-Race Model

- 77086-4 X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®

Rear Suspension

- 7726 Bulkhead tie bar, upper (1)/ lower (2) (steel)
- 7727X Bulkhead, rear (upper & lower), center differential (replacing #7727 & #7728 requires #5107A ball bearings (2))
- 7752 Carriers, stub axle (left & right)
- 7716 Mount, tie bar, front (1)/ rear (1)
- 7738 Shock tower, rear (left & right halves)
- 7731 Suspension arms, lower (left, front or rear) (1)
- 7730 Suspension arms, lower (right, front or rear) (1)
- 7729 Suspension arms, upper (left or right, front or rear) (2)
- 7743 Suspension pin retainer (4)
- 7740 Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)
- 7742 Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)
- 7741 Suspension pins, 4x85mm (hardened steel) (2)

Shocks (GTX)

- 7765A Body, GTX shock (aluminum, black-anodized) (1)
- 7765 Body, GTX shock (aluminum, blue-anodized) (1)
- 7765G Body, GTX shock (aluminum, green-anodized) (1)
- 7765R Body, GTX shock (aluminum, red-anodized) (1)
- 7765X Body, GTX shock (hard-anodized, PTFE-coated aluminum) (1)
- 7762 Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks)
- 7763 Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2)
- 7763T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls)
- 7764A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8)
- 7764G Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8)
- 7764X Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8)
- 7764R Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)
- 7764 Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks)
- 7761A Shocks, GTX, aluminum (black-anodized) (fully assembled w/o springs) (2)
- 7761 Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o springs) (2)
- 7761G Shocks, GTX, aluminum (green-anodized) (fully assembled w/o springs) (2)
- 7761R Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)
- 1667 Silicone shock oil (30 wt), 60cc
- 7767 Spring retainer (adjuster), blue-anodized aluminum, GTX shocks (4) (assembled with o-ring)
- 7767G Spring retainer (adjuster), green-anodized aluminum, GTX shocks (4) (assembled with o-ring)
- 7767X Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks (4) (assembled with o-ring)
- 7767R Spring retainer (adjuster), red-anodized aluminum, GTX shocks (4) (assembled with o-ring)
- 7853 Springs, shock (natural finish) (GTX) (0.824 rate) (2)
- 7854 Springs, shock (natural finish) (GTX) (0.929 rate) (2)
- 7766 Springs, shock (natural finish) (GTX) (1.055 rate) (2)
- 7855 Springs, shock (natural finish) (GTX) (1.199 rate) (2)

Page 3 X-Maxx: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

- 7856 Springs, shock (natural finish) (GTX) (1.346 rate) (2)
7857 Springs, shock (natural finish) (GTX) (1.450 rate) (2)
7858 Springs, shock (natural finish) (GTX) (1.538 rate) (2)

Spur Gears & Pinion Gears

- 6484X Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6485X Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6486X Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6488X Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6487X Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6489X Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6490X Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6491X Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6494X Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6495X Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6496X Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6447X Spur gear, 46-tooth, steel (1.0 metric pitch)
6448X Spur gear, 50-tooth, steel (1.0 metric pitch)
6449X Spur gear, 54-tooth, steel (1.0 metric pitch)

Steering Components

- 5119 Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116 Ball bearings, blue rubber sealed (5x11x4mm) (2)
7747 Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
7746 Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
7746X Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo)
7748 Toe links, molded composite, 173mm (158mm center to center) (black) (2)
7748X Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748G Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

Suspension Linkage

- 7798 Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert)
7797 Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)
7743 Suspension pin retainer (4)
7740 Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)
7742 Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)
7741 Suspension pins, 4x85mm (hardened steel) (2)
7748 Toe links, molded composite, 173mm (158mm center to center) (black) (2)
7748X Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748G Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

Team Traxxas Items

- 2514 Decal sheet, racing sponsors
9950 Official Team Traxxas® racing decal set (flag logo/ 6-color)
9909 Traxxas® racing banner, red & black (3x7 feet)

Tires & Wheels

- 7772A Tires & wheels, assembled, glued (X-Maxx® black chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)

- 7772X Tires & wheels, assembled, glued (X-Maxx® black wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7773 Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2)
7772G Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7772T Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7772R Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7770X Tires, Maxx® AT (left & right) (2)/ foam inserts (2)
7757 Wheel hex clips (6)
7756 Wheel hubs, hex (2)/ hex clips (2)
7756X Wheel hubs, hex, aluminum (blue-anodized) (4)
7756G Wheel hubs, hex, aluminum (green-anodized) (4)
7756R Wheel hubs, hex, aluminum (red-anodized) (4)
7758A Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
7758 Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
7758G Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
7758R Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
7771 Wheels, X-Maxx®, black (left & right)

Transmission Components

- 7796 Center drive, torque-biasing (assembled)/ 17x26x5 ball bearings (2) (requires #7727X bulkheads)
7787 Covers, gear (3)
7785X Input gear, transmission, 20-tooth/ 2.5x12mm pin
7786X Input shaft, transmission (cush drive)
5040 Oil, differential (20M weight) (standard)
7784X Output gear, 51-tooth, metal (requires #7785X input gear)

Traxxas Tools

- 3433X Body reamer (aluminum handle)
3433 Body reamer (plastic handle)
3436 Cap, body reamer
3432 Scissors, curved tip
3431 Scissors, straight tip
8712 Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
8722 Speed bit handle, premium (rubber overmold)
8711 Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8719 Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716 Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive
8715 Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
3415 Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle)

Turnbuckles & Threaded Rods

- 7798 Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert)
7797 Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)
7748 Toe links, molded composite, 173mm (158mm center to center) (black) (2)
7748X Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748G Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)