MANUF / DIST:

PREPARER PHONE: 24 HR EMERGENCY PHONE: TRADE NAME / SYNONYMS:

CHEMICAL NAME / SYNONYMS:

CHEMICAL FAMILY: FORMULA: PRODUCT CODE:

## **SECTION 1 - IDENTIFICATION**

ZAPPY'S AUTO WASHES 8806 MENTOR AVE, UNIT D MENTOR, OH 44060

844-927-9274 INFOTRAC 1-800-535-5053

# HEAVY DUTY BLAZIN' WHEEL

CLEANER

NOT APPLICABLE


NOT APPLICABLE

PROPRIETARY

CLN\_105

## SECTION 2. HAZARDOUS IDENTIFICATION

# HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:



Signal Word: DANGER! - FOR HEALTH EFFECTS (Acute and Chronic): SEE SECTION 11

# SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: see CFR29\1910.1200 (D-(13) [exact % withheld as trade secret ]						
CHEMICAL / COMMON NAME	CAS#	PERCENTAGE PEL-OSHA	TLV-ACGIH			
Potassium Hydroxide	1310-58-3	N.E	2mg/m3			
2 Butoxy Ethanol (Skin)	111-76-2	50PPM		25PPM		
Confidential and Trade Secret Surfactants non Hazardous content.						
THIS PRODUCT HAS NO CARCINOGENS (ARC, OSHA, IARC)						

## **SECTION 4 - FIRST AID MEASURES**

#### EMERGENCY FIRST AID PROCEDURES:

- a) Skin Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.
- b) Eyes Flush immediately with large quantities of running water for at least 15 minutes. Consult physician.
- c) Inhalation If affected, remove individual to fresh air. If breathing Is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d) Ingestion Do not induce vomiting. Call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

## **SECTION 5 - FIRE FIGHTING MEASURES**

#### EXTINGUISHING MEDIA: N/A

SPECIAL FIRE FIGHTING PROCEDURES: N/A

#### UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

#### INCOMPATIBILITY (Material To Avoid):

Avoid contact with acids and strong oxidizers such as permanganate, chlorine, ectoderm.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Absorb the large spill on suitable absorbent. Wash the residue down the Drain or pit with plenty of water. Small spills can be flushed down the drain with plenty of water

## SECTION 7 - HANDLING AND STORAGE

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- ) Do not store under freezing conditions or above 120 degrees F.
- B) Protect from physical damage and keep tightly closed.
- C) Do not store near acids or acidic materials and oxidizers.
- D) Containers marked Compounds cleaning liquid, 8, NAI 760 Corrosive.

HAZARDOUS DECOMPOSITION PRODUCTS:	None	CONDITIONS TO AVOID FOR POLYMERIZATION:	N/A
CONDITIONS TO AVOID FOR STABILITY:	N/A		

MECHANICAL (General) : N/A

#### SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

N/A

VENTILATION:	
LOCAL EXHAUST	Below TIN(s)
SPECIAL:	N/A
RESPIRATORY PR	OTECTION:

An appropriate NIOSH approved hydrocarbon canister or respirator for organic vapor should be worn if needed. PROTECTIVE GLOVES:

OTHER:

Wear - resistant gloves such as nitrification rubber, PVC, etc.. OTHER PROTECTIVE EQUIPMENT:

Eye wash and quick drench facilities.

#### OTHER ENGINEERING CONTROLS: None Known

#### WORK PRACTICES:

Eye wash fountain and safety shower should be easily accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate ventilation.

#### HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT VAPOR PRESSURE (mmHg):	>212 ND	SPECIFIC GRAVITY (WATER-I): PERCENT VOLATILE BY VOLUME $\%$ .	> 80.00
VAPOR DENSITY (AIR-I):	ND	EVAPORATION RATE (WATER-I):	
SOLUBILITY IN WATER	100%	FLAMMABLE LIMITS: Lel= N/A UEL= N/A	
FLASH POINT (Method Used):	None	рН	12
Malting $pt_N/A$ /freezing $pt_30+ {}^{0}E/B$ alative density N/A			

Melting pt-N/A /freezing pt 30+-<sup>0</sup>F/Relative density N/A

APPEARANCE, ODOR, VISCOSITY:: Thin Dark Orange colored liquid with Cinnamon scent.

## SECTION 10 - STABILITY AND REACTIVITY

#### HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

THIS PRODUCF IS STABLE

# SECTION 11 - TOXICOLOGICAL INFORMATION

## FOR NUMERICAL MEASURES OF TOXICITY SEE SECTION 3, COLUMNS(PEL-OSHA)AND(TLV-ACGIH) HEALTH EFFECTS (Acute and Chronic): ALKALINE SUBSTANCE

\*Acute\*:

a) Eyes -Can cause severe irritation, redness, tearing, blurred vision.

b) Skin - Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

c) Inhalation - Breathing of dust or mist can cause mild to severe irritation of nasal or respiratory passage.

d) Ingestion - Can cause gastronomies-intestinal irritation, nausea, vomiting and diarrhea.

#### \*Chronic\*

a) Overexposure to glycol ethers (in its pure state) has been found to cause anemia, liver abnormalities, kidney damage, lung damage and blood abnormalities in laboratory animals.

PRIMARY ROUTES OF ENTRY:

a) Skin b) Inhalation

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA)

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

# SECTION 12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: N/A

100% BIODEGRADABLE

ECOTOXICOLOGICAL INFORMATION: N/A

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHODS: Dispose of according to local, state and federal regulations for biodegradable detergents.

**SECTION 14 - TRANSPORT INFORMATION** 

ADDITIONAL COMMENTS:

SHIPPING INFO, UN/NA #'s, SECONDARY LABEL INFO NECESSARY OR SUGGESTED.

# <u>COMPOUNDS. CLEANING LIQUID. 8. NA-1760 PG 11. CORROSIVE</u> (Potassium Hydroxide).

# KEEP OUT OF THE REACH OF CHILDREN!

## SECTION 15 - REGULATORY INFORMATION

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA)

## SECTION 16 - OTHER INFORMATION

## KEEP OUT OF THE REACH OF CHILDREN!

IN CLOSE COOPERATION OF THE US GOVERNMENT'S PAPER REDUCTION ACT, AND ALSO IN EFFORT TO

PROVIDE FULL AND COMPLETE INFORMATION AS SUGGESTED BY THE OSHA GUIDELINES , AND KEEPING IN ALIGNMENT WITH THE SOCIETY CHEMICAL HAZARD COMMUNICATION (SCHC) AND WE HAVE BEEN ABLE TO KEEP ALL IN 4 PAGES..

# THESE SDS SHEETS ARE WRITTEN IN AN EFFORT TO PROVIDE INFORMATION TO THE WORKER IN THE WORKPLACE AND IN SUCH A WAY IT CAN BE UNDERSTOOD.

We have enjoyed many compliments as to the readability and understandable content, and take great pride in providing these Safety Data Sheets to the use of our customers.

The International Labour Organization has suggested 16 sections of the sheets, and we have re adjusted the 8 part, and rearranged the information, and renamed the sheets from MATERIAL Safety Data Sheets to SAFETY DATA SHEETS. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. IT IS PROVIDED FOR A CONTINUING SAFETY PROGRAM INITIATED BY THE MANUFACTURER/DISTRIBUTOR NAMED ON THIS SHEET. IT IS NOT INTENDED TO CONSTITUTE PERFORMANCE INFORMATION CONCERNING THE PRODUCT. NO EXPRESS WARRANTY, OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE WITH RESPECT TO THE PRODUCT OR THE INFORMATION CONTAINED HEREIN.

Please note that several items were left out of section 9 because they do not affect the worker in the workplace. Partition coefficient: n-octanol/water; • Auto-ignition temperature; • Decomposition temperature and Odor threshold.