

QC7I-MH

HEAD AND CARTRIDGE SOLD SEPARATELY

QC71 HEAD W/ GAUGE & SHUTOFF PART NO. EV9272-41 MH REPL. CART. (1 PK) EV9613-01 MH REPL. CART. (6 PK) EV9613-06

SYSTEM DETAILS

SHIPPING WEIGHT (HEAD & CARTRIDGE), LBS: 8
DPERATING WEIGHT, LBS: 8
MAX. FLOW RATE, GPM: 1.67
MAX. WORKING PRESSURE, PSI: 125
MAX. OPERATIONAL TEMP, 'F: 100

NOTES:

- (1) ITEMS SHOWN IN BROKEN LINES TO BE FURNISHED BY OTHERS.
- (2) ALL DIMENSIONS ARE \pm 1 INCH (25mm) AND SUBJECT TO CHANGE WITHOUT NOTICE.
- (3) ALLOW MINIMUM 2.5 INCHES BELOW SYSTEM FOR CARTRIDGE CHANGE.

DO NOT SCALE DRAWING TOLERANCES: ±1/8 UNLESS DTHERWISE NOTED						QC/I-MH Q.5 MICRON PRE-COAT FILTER				
Ŧ.	Changa	Ву	Арр	Date	ENGINEERED SYSTEMS	TECHNICAL DATA SHEET				
					NORTHBROOK, ILLINOIS PRINT AND BILL OF WATERAL ARE NOT	DΕ	TAILED BY:	_ A	VPP. BY:	SHEET
						KVIR	6/28/02			1 OF
					TO BE USED WITHOUT THE WRITTEN	REF. NO.		7	PART ND.	
					CONSENT OF CULLIGAN INTERNATIONAL CO.				QC7I-	-мн