

QC7I-MC SINGLE

PART NO. EV9275-01

REPL. CART. (1 PK) EV9612-06 REPL. CART. (6 PK) EV9612-05

SYSTEM DETAILS

SHIPPING WEIGHT, LBS: 7
OPERATING WEIGHT, LBS: 8
MAX. FLOW RATE, GPM: 1.67

MAX. WORKING PRESSURE, PSI: 125
MAX. OPERATIONAL TEMP, *F: 100

NOTES:

- (1) ITEMS SHOWN IN BROKEN LINES TO BE FURNISHED BY OTHERS.
- (2) ALL DIMENSIONS ARE \pm 1 INCH (25mm) AND SUBJECT TO CHANGE WITHOUT NOTICE.
- (3) ALLOW MINIMUM 2.5 INCHES BELOW SYSTEM FOR CARTRIDGE CHANGE.

	DO NOT SCALE DRAV TOLERANCES: ±1/8" UNLESS O	MING THER	WISE	NOTED	
-	Change	Βу	Арф	Date	ENGINEERED SYSTEMS
					NORTHBROOK, ILLINOIS
					PRINT AND BILL OF MATERIAL ARE NOT
					TO BE USED WITHOUT THE WRITTEN
					I CONSENT OF CULLICAN INTERNATIONAL CO

•	O.5 MICRON PRE—COAT FILTER TECHNICAL DATA SHEET					
	DETAILED BY: KNR 5/17/02		SHEET 1 OF 1			
	REF. ND.	PART NO.	1404			

OCTILING CINCLE