



INSURICE 2000 SINGLE

PART NO. EV9324-01
 REPL. CART. {1 PK} EV9612-21
 REPL. CART. {6 PK} EV9612-26

SYSTEM DETAILS

SHIPPING WEIGHT, LBS: 7
 OPERATING WEIGHT, LBS: 9
 MAX. FLOW RATE, GPM: 1.67
 MAX. WORKING PRESSURE, PSI: 125
 MAX. OPERATIONAL TEMP, °F: 100

NOTES:

- (1) ITEMS SHOWN IN BROKEN LINES TO BE FURNISHED BY OTHERS.
- (2) ALL DIMENSIONS ARE ± 1 INCH (25mm) AND SUBJECT TO CHANGE WITHOUT NOTICE.
- (3) ALLOW MINIMUM 2.5 INCHES BELOW SYSTEM FOR CARTRIDGE CHANGE.

DO NOT SCALE DRAWING TOLERANCES: ±1/8" UNLESS OTHERWISE NOTED					 ENGINEERED SYSTEMS NORTHBROOK, ILLINOIS <small>PRINT AND BILL OF MATERIAL ARE NOT TO BE USED WITHOUT THE WRITTEN CONSENT OF CULLIGAN INTERNATIONAL CO.</small>	NAME: INSURICE 2000 SINGLE 0.5 MICRON PRE-COAT FILTER TECHNICAL DATA SHEET		
Rev.	Change	By	App	Date		DETAILED BY: KMY 8/17/02	APP. BY:	SHEET 1 OF 1
						REF. NO.	PART NO.	
							INSURICE_2000_1	