

INSURICE 4000 TRIPLE


PART NO. EV9325-03
 REPL. CART. (1 PK) EV9612-31
 REPL. CART. (6 PK) EV9612-36

SYSTEM DETAILS

SHIPPING WEIGHT, LBS: 23
 OPERATING WEIGHT, LBS: 38
 MAX. FLOW RATE, GPM: 5.0
 MAX. WORKING PRESSURE, PSI: 125
 MAX. OPERATIONAL TEMP, °F: 100

NOTES:

- (1) ITEMS SHOWN IN BROKEN LINES TO BE FURNISHED BY OTHERS.
- (2) ALL DIMENSIONS ARE ± 1 INCH (25mm) AND SUBJECT TO CHANGE WITHOUT NOTICE.
- (3) ALLOW MINIMUM 2.5 INCHES BELOW SYSTEM FOR CARTRIDGE CHANGE.

DO NOT SCALE DRAWING TOLERANCES: ±1/8" UNLESS OTHERWISE NOTED					 ENGINEERED SYSTEMS NORTHBROOK, ILLINOIS	NAME INSURICE 4000 TRIPLE 0.5 MICRON PRE-COAT FILTER TECHNICAL DATA SHEET		
Rev.	Change	By	App	Date		DETAILED BY: KNR 6/17/02	APP. BY:	SHEET 1 OF 1
PRINT AND BILL OF MATERIAL ARE NOT TO BE USED WITHOUT THE WRITTEN CONSENT OF CULLIGAN INTERNATIONAL CO.					REF. NO.	PART NO. INSURICE_4000_3		