

Filter Housing Selection Guide

[Click on Links](#)

SB

HP

INV

SBHF

SB/HP/INV/SBHF Hurricane® Housings

Industrial/Municipal (SB/INV) Commercial (HP)

- ▶ Combination cyclone separator and cartridge filter in a single design
- ▶ Saves up to 20% in energy costs
- ▶ Flow rates to 1,900 GPM (INV); 1,200 GPM (SB); 150 GPM (HP); 2,400 GPM (SBHF)

NSF NSF-61 Listed

[View Hurricane® Animation](#)



WB

WB 5x

WBC

WB/WBC/WB 5x170FL WaterBetter® Housings

Commercial

- ▶ Single cartridge design
- ▶ Patented Up-flow design
- ▶ Coated option available
- ▶ Flow rates to 150 GPM (WB/WBC); 600 GPM (WB 5x170FL)

▶ Offered in 304/316 stainless steel

NSF NSF-61 Listed (excluding WB 5x170FL)



HMC

HMC Filter Housings

Industrial/Municipal

- ▶ Built to ASME design standards
- ▶ U-Stamp option available
- ▶ Standard hold down plates to accept DOE, 222/Flat and 222/Fin style cartridges
- ▶ Flow rates to 1,400 GPM
- ▶ Offered in 304/316 stainless steel



HIF

HIF Filter Housings

Commercial

- ▶ Patented Up-flow design
- ▶ Coated option available
- ▶ Flow rates to 800 GPM
- ▶ Offered in 304/316 stainless steel

NSF NSF-61 Listed



BC

HBC

BC/HBC Band Clamp Housings

Commercial

- ▶ FNPT, BSTP, Flange and Victaulic connections available (BC series only)
- ▶ Patented Up-flow design (BC series only)
- ▶ Flow rates to 600 GPM
- ▶ Offered in 304/316 stainless steel



FSSS

FSSS Single Cartridge Housings

Commercial/Industrial

- ▶ Designed for 300 PSI
- ▶ DOE or 222/Flat configurations available
- ▶ Offered in 304/316 stainless steel



HMB

HSB

BCB

HMB/HSB/BCB Bag Housings

Industrial/Municipal

- ▶ U-Stamp option available (HMB, HSB)
- ▶ Standard #1, #2 and Extended bag options
- ▶ Flow rates to 2,400 GPM
- ▶ Offered in 304/316 stainless steel



WW

COAT

Specialty Housings

- ▶ WW - combined housing/heat exchanger
- ▶ COAT - fusion-bonded epoxy coating option



NSF

NSF Listed Filter Housings



FS

Filtration Systems



Note: This publication is to be used as a guide. The data within has been obtained from many sources and is considered to be accurate. Harmsco does not assume liability for the accuracy and/or completeness of this data. Changes to the data can be made without notification. Temperature, Pressure, Flow Rates, Differential Pressures, Chemical Combinations and other unknown factors can affect performance in unknown ways. **Limited Warranty:** Harmsco warrants their products to be free of material and workmanship defects. Determination of suitability of Harmsco products for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. The end user/installer/buyer shall be liable for the product's performance and suitability regarding their specific intended applications. End users should perform their own tests to determine suitability for each application.