



EVERPURE® SCS-350

SCS-350 FOR YOUR COFFEE AT HOME

The same commercial quality that makes Pentair® Everpure® the overwhelming choice for water filtration in restaurants is also available for your entire home, including the coffee maker. The SCS-350 addresses the issues associated with water quality in home coffee makers. This system is designed for use with high-end residential coffee and espresso brewing machines.

150
gallons
CAPACITY
568 Litres

FEATURES

Commercial Grade Filtration

- High capacity Fibredyne carbon block enhances chlorine taste while reducing odor to provide your coffee/espresso with high quality brewing water
- Provides softened, buffered and filtered water for quality brewing



Added Benefits

- Reduces hardness in water that can cause mineral build-up in coffee and espresso equipment

Easy Installation

- Sanitary cartridge replacement is simple, quick and clean

SPECIFICATIONS

- **Flow rate**
controlled at 0.5 gpm (1.9 Lpm)[†]
- **Temperature**
35-100° F (2-38° C)
cold water use only
- **Pressure**
10-125 psi (0.7-8.6 bar)
non-shock
- **Capacity**
150 gal. (568 L)
- **Dimensions**
5W x 27H x 5D in
(13W x 69H x 13D cm)

SUBSTANCE REDUCTION

- Calcium
- Magnesium
- Chlorine taste & odor

EPA EST. NO. 002623-IL-002

ORDERING INFORMATION

MODEL	PART NO	DESCRIPTION
SCS-350	EV927020	Cartridge



GENERAL INSTALLATION / OPERATION / MAINTENANCE REQUIREMENTS

This drinking water system must be maintained according to the manufacturer's instructions, including replacement of filter cartridges. The substances reduced or removed by this system are not necessarily in your water. Read the performance data sheet.

It is recommended that before purchasing a water treatment unit, you have your water tested to determine your actual treatment needs.

Space required: 5W x 27H x 5D in (13W x 69H x 13D cm) including 2-1/2 inches of clear space under unit for cartridge change.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

Install vertically with cartridge hanging down.

Use minimum length of tubing possible.

Flush new cartridge at full flow for three minutes to purge air.

Replace cartridge when capacity is reached, or when flow becomes too slow. To ensure optimum water filtration, cartridges should be changed annually.

System comes complete with filter cartridge, head, fittings, and connector.

OPTIONS

SCS-350 FILTRATION/DECALCIFICATION SERVICE KIT (PN: EV925230)

Kit contains all of the components needed to install filtration for new built-in coffee appliances. These include a QL3 head, JT cartridge, SCS-350 cartridge, bypass plug, Scalekleen, angle stop valve adaptor, special fittings, tubing and instructions.

STANDARD FILTRATION/DECALCIFICATION SERVICE KIT (PN: EV925240)

Kit contains all of the components needed by the Service Agent to service existing built-in coffee appliances. These include a QL3 head, JT cartridge, bypass plug, Scalekleen, special fittings, tubing and instructions.



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | WWW.RESIDENTIAL.EVERPURE.COM | CUSTOMER CARE: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4002875 REV D JL14 © 2014 Pentair Residential Filtration, LLC. All Rights Reserved.