


Spray Hose [KS-20]



Applications 用途

- Agricultural chemicals sprayer
农业喷洒等领域
- High pressure discharge hose
高压排放软管
- Painting
油漆喷涂
- Conveying chemicals
输送喷射性的油漆, 汽车烤漆, 瓷漆, 稀释剂, 松节油, 空气, 油等, 许多溶剂和化学品

Features 特征

- High pressure resistance
耐压性极强
- Flexibility
弯曲性高
- Soft and light
柔软, 轻便
- Superior UV, wear, chemical resistance
对阳光, 外环境, 化学物耐性很强

Standard Specification 详细

Item No.	Nominal Size		Inner diameter (mm)	Outer diameter (mm)	Length (roll) (m)	Working Pressure (at 20°C) (kg/cm ²)
	(mm)	(inch)				
KS20-07	7.5	-	7.5	13.5	100-300	40
KS20-08	8.5	5/16"	8.5	14.5	100-300	50
KS20-10	10	3/8"	10	16	50-200	50
KS20-13	13	1/2"	13	20	50-200	40
KS20-16	16	5/8"	16	24	50-100	30
KS20-19	19	3/4"	19	28	50-100	30
KS20-25	25	1"	25	33	50-100	20

Order production is possible (可订造)*