

FLOOR PERFORMANCE BAR

Instruction manual

Thank you very much for purchasing Beatrush product.

Please read well this manual to use the product safely and correctly and keep it with the automobile inspection certificate.

Model	Chassis Code	Part No.
SUBARU IMPREZA	GC8 / GDA / GDB	S86010PB-C

- Read the instruction manual carefully and install the part only if you understand the instructions.
- Keep the instruction manual in a safe place; we do not replace them if you lose or misplaced them.
- For safety reasons follow these instructions and all safety procedures.
- Product design improvement and instruction changes may be made without notice.
- Please follow the product's given instructions, do not use other references when installing our products.
- The drawings in the instruction manual may not be fully detailed and may be abstract.
- If you find a problem and/or are uncertain about these instructions please contact us.

∴ Safety Rules When Handling the Product

- Our products are built for the Japanese market and may not precisely fit foreign markets; please make sure the product fits properly before you install it.
- Any alterations or modifications to our products are prohibited.
- Before installing or using our products make sure to read the products instruction manual.
- Installation must be performed by licensed mechanics.
- We are not responsible for any damages done to our products by a licensed mechanic and/or anyone else who installs the product.
- Follow the instruction manual step by step for installation; do not use other instructions for installation.
- Do not work with fire.
- If the instructions ask for original parts, make sure to use the parts asked for.
- When tightening bolts and nuts follow the cars manufacturers measurements.
- Do not work with the engine on and/or a heated engine.
- Mechanics must work carefully and wear appropriate clothes, such as helmets, goggles, etc. when installing the product.
- When installing the product work on a flat surface; when lifting the car make sure to use a ridge rack and jack where the cars manufacturer tells to do so.

[WARNING]

Laile assumes no responsibility for damage, accidents, injuries or death resulting from the improper installation, assembly, misuse, and/or modification of the product.



LAILE Co.,Ltd.

335 Hirato-cho, Totsuka-ku, Yokohama-City, KANAGAWA 244-0803 JAPAN tel +81-45-824-1835 customer@laile.co.ip

COMPLETE PARTS

	Parts Name	Qty.	y. Parts Name		Qty.
1	SHAFT	2	9	M8 Spring Lock Washer	6
2	CENTER BRACKET	1	10	M8 Plain Washer	6
3	CENTER JOINT BRACKET / Rh	1	11)	M8 Hexagon Nuts with Flange	2
4	CENTER JOINT BRACKET / Lh	1	12	M10×45 Hexagon Socket Button Head Screws	4
(5)	SIDE BRACKET / Rh	1	13	M10 Spring Lock Washer	4
6	SIDE BRACKET / Lh	1	14)	M10 Plain Washer	8
7	M8×25 Hexagon Socket Button Head Screws	2	15)	M10 Nylon Insert Lock Nut	4
8	M8×20 Hexagon Socket Button Head Screws	4	16	Attached Band	1


INSTALL ATION


- When this product is installed, please work according to the maintenance manual of the automaker issue.
- When this product is installed, please be careful not to damaged the genuine parts.
- 1. Jack the vehicle up and detatch the driver's seat, passenger seat, back seat, center consol and floor carpet.
- 2. Detach the side brake wire from side brake lever and detach the side brake wirecramp.
- 3. Install the center mount bracket temporarily with original screws. Mark in the point where make a hole in the floor, detach the mount bracket and make a hole about ϕ 9mm with drill etc.



Attention: Confirm the location which are wiring and laying of the pipes etx. in an interior and outsides, and work so as not to put a bruise. Do do a rust stop after making the hole.

- 4. Fix the center mount bracket with te side brakce wire cramp with original screws and the attached screws.
- 5. Install the side mount bracket temporarily with original bolt fixing the seat belt.
- 6.Install the right and left shaft to mount bracket, tighten all the screws and fix it.
- 7. Install the firstly detached original parts.





 If wiring intervenes when installing a side mount bracket, move the wiring and fix it by attached binding band.

Side Bracket (Right side)