## **MODEL**

| Maximum Speed¹ Up to 3.6 mph  Ground Clearance³ 3" at motor  Turning Radius³ 24.25"  Overall Length³ 40"  Overall Width³ 23.5"  Seat-to-Ground Height 14.5" (no adjustment)  Casters 8" solid  Drive Tires 12" Pneumatic drive  Suspension Limited Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.)  Total Weight Without Batteries³.5 4 lbs. (unit does not disassemble)  Theaviest Piece When Disassembled³ N/A (unit does not disassemble)  Standard Seating Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical Standard Electronics 50 amp, PG VSI  Battery (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion  Battery Weight⁴ 7 lbs. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger 2-amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                       | Jazzy Passport <sup>6</sup>     | K0899                                         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-----------------------------------------------|
| Ground Clearance <sup>3</sup> 3" at motor  Turning Radius <sup>3</sup> 24.25"  Overall Length <sup>3</sup> 40"  Overall Width <sup>3</sup> 23.5"  Seat-to-Ground Height Seat-to-Foot Platform Height  Casters 8" solid  Drive Tires 12" Pneumatic drive  Suspension Limited  Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) For tall Weight Without Batteries <sup>3,5</sup> Heaviest Piece When Disassembled <sup>3</sup> Standard Seating Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical Standard Electronics 50 amp, PG VSI  Battery (1) 24V 18 AH Lithium ion Requirements <sup>3</sup> (1) 25.2V 10.4 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month Electronics: 13-month                                                                                                                                  | Weight Capacity                 | 250 lbs.                                      |
| Turning Radius³ 24.25″  Overall Length³ 40″  Overall Width³ 23.5″  Seat-to-Ground Height Seat-to-Foot Platform Height  Casters 8″ solid  Drive Tires 12″ Pneumatic drive  Suspension Limited  Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 250 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.)  Heaviest Piece When Disassembled³  Standard Seating Material: Black, Foam Dimensions: 17.5″ x 16.5″  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical Standard Electronics 50 amp, PG VSI  Battery (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (2) 2-amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                  | Maximum Speed <sup>1</sup>      | Up to 3.6 mph                                 |
| Overall Length³ Overall Width³ 23.5"  Seat-to-Ground Height Seat-to-Foot Platform Height  Casters  B" solid  Drive Tires 12" Pneumatic drive  Suspension  Limited Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Total Weight Without Batteries³.5  Heaviest Piece When Disassembled³  Standard Seating  Drivetrain  Two-motor, rear-wheel drive  Dual Braking System  Standard Electronics  Battery Requirements³  (1) 24V 18 AH Lithium ion (25.2V 10.4 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  Varanty  Waranty  Waranty  40"  19"  14.5" (no adjustment)  15.0 AH Eithium electronics 15.0 amp, PG VSI  Battery Charger  10.4 AH Lithium ion (air safe travel battery)  Battery Charger  2-amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month       | Ground Clearance <sup>3</sup>   | 3" at motor                                   |
| Overall Width³  Seat-to-Ground Height  Seat-to-Foot Platform Height  Casters  8" solid  Drive Tires  12" Pneumatic drive  Suspension  Limited  Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.)  Total Weight Without Batteries³. 5  Heaviest Piece When Disassembled³  N/A (unit does not disassemble)  Standard Seating  Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain  Two-motor, rear-wheel drive  Dual Braking System  Regenerative and electromechanical  Standard Electronics  50 amp, PG VSI  Battery  Requirements³  (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion  7 lbs. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  2-amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                  | Turning Radius <sup>3</sup>     | 24.25"                                        |
| Seat-to-Ground Height Seat-to-Foot Platform Height Casters  8" solid  Drive Tires 12" Pneumatic drive  Suspension Limited Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Fotal Weight Without Batteries <sup>3, 5</sup> Heaviest Piece When Disassembled <sup>3</sup> N/A (unit does not disassemble)  Standard Seating Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical  Standard Electronics 50 amp, PG VSI  Battery Requirements <sup>3</sup> (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion Battery Weight <sup>4</sup> 52 lbs. 10.4 AH Lithium ion (air safe travel battery) Battery Charger  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                  | Overall Length <sup>3</sup>     | 40"                                           |
| Height Seat-to-Foot Platform Height Casters  8" solid Drive Tires 12" Pneumatic drive Suspension Limited Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Heaviest Piece When Disassembled³ N/A (unit does not disassemble)  Standard Seating Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical Standard Electronics 50 amp, PG VSI Battery Requirements³ (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (2) 2-amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                           | Overall Width <sup>3</sup>      | 23.5"                                         |
| Platform Height Casters  8" solid Drive Tires 12" Pneumatic drive Suspension Limited Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Total Weight Without Batteries3.5 Heaviest Piece When Disassembled3 N/A (unit does not disassemble)  Standard Seating Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical Standard Electronics 50 amp, PG VSI Battery Requirements3 (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion Flos. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery) Battery Charger  Varanty  Waranty  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                               |                                 | 19"                                           |
| Drive Tires  12" Pneumatic drive  Limited  Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH W 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.)  Total Weight Without Batteries³, 5 Heaviest Piece When Disassembled³  Standard Seating  Drivetrain  Drivetrain  Dual Braking System  Regenerative and electromechanical  Standard Electronics  50 amp, PG VSI  Battery Requirements³  Battery Weight⁴  Total Weight Waranty  12" Pneumatic drive  Up to 9.6 miles (18 AH @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.)  54 lbs. (unit does not disassemble)  Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain  Two-motor, rear-wheel drive  Regenerative and electromechanical  Standard Electronics  50 amp, PG VSI  Battery  Requirements³  Total Weight⁴  Total Waranty  12" Pneumatic drive  18 AH electronics  18 AH electronics  19 AH Lithium ion (air safe travel battery)  Prame: 5-year limited Drivetrain: 13-month Electronics: 13-month |                                 | 14.5" (no adjustment)                         |
| Range Per Charge <sup>1,2</sup> Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 1.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.) Total Weight Without Batteries <sup>3,5</sup> 54 lbs. (unit does not disassemble)  N/A (unit does not disassemble)  Standard Seating Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical  Standard Electronics 50 amp, PG VSI  Battery Requirements <sup>3</sup> (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion Flos. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  Prame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                | Casters                         | 8" solid                                      |
| Range Per Charge <sup>1,2</sup> Up to 9.6 miles (18 AH @ 250 lbs.) Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.)  Total Weight Without Batteries <sup>3,5</sup> Heaviest Piece When Disassembled <sup>3</sup> N/A (unit does not disassemble)  Standard Seating Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical  Standard Electronics 50 amp, PG VSI  Battery Requirements <sup>3</sup> (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  Prame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                                                         | Drive Tires                     | 12" Pneumatic drive                           |
| Range Per Charge <sup>1,2</sup> Up to 11 miles (18 AH @ 200 lbs.) Up to 5.7 miles (10.4 AH travel battery @ 250 lbs.) Up to 6.3 miles (10.4 AH travel battery @ 200 lbs.)  Total Weight Without Batteries <sup>3,5</sup> Heaviest Piece When Disassembled <sup>3</sup> N/A (unit does not disassemble)  Standard Seating Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain Two-motor, rear-wheel drive  Dual Braking System Regenerative and electromechanical  Standard Electronics 50 amp, PG VSI  Battery Requirements <sup>3</sup> (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  Varanty  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                   | Suspension                      | Limited                                       |
| Without Batteries <sup>3, 5</sup> Heaviest Piece When Disassembled <sup>3</sup> Standard Seating  Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain  Two-motor, rear-wheel drive  Dual Braking System  Regenerative and electromechanical  Standard Electronics  Battery Requirements <sup>3</sup> (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion  Flos. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  Waranty  Waranty  Waranty  N/A (unit does not disassemble)  N/A (unit does not disassemble)  N/A (unit does not disassemble)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Range Per Charge <sup>1,2</sup> |                                               |
| When Disassembled³  Standard Seating  Material: Black, Foam Dimensions: 17.5" x 16.5"  Drivetrain  Two-motor, rear-wheel drive  Dual Braking System  Regenerative and electromechanical  Standard Electronics  Battery  Requirements³  (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion  Fattery Weight⁴  Battery Charger  Two-motor, rear-wheel drive  Regenerative and electromechanical  10 25.2V 10.4 AH Lithium ion  Flos. 18 AH  5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  Frame: 5-year limited  Drivetrain: 13-month  Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                 | 54 lbs. (unit does not disassemble)           |
| Dimensions: 17.5" x 16.5"  Drivetrain  Dual Braking System  Regenerative and electromechanical  Standard Electronics  Battery  Requirements³  (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion  Battery Weight⁴  Battery Charger  Trunce 1.2 - amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                 | N/A (unit does not disassemble)               |
| Dual Braking System  Regenerative and electromechanical  Standard Electronics  50 amp, PG VSI  Battery  Requirements³  (1) 24V 18 AH Lithium ion  (1) 25.2V 10.4 AH Lithium ion  7 lbs. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  2-amp, off-board  Frame: 5-year limited  Drivetrain: 13-month  Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Standard Seating                |                                               |
| Standard Electronics 50 amp, PG VSI  Battery (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion  Battery Weight <sup>4</sup> 7 lbs. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger 2-amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Drivetrain                      | Two-motor, rear-wheel drive                   |
| Battery Requirements³ (1) 24V 18 AH Lithium ion (1) 25.2V 10.4 AH Lithium ion 7 lbs. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger 2-amp, off-board Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | <b>Dual Braking System</b>      | Regenerative and electromechanical            |
| Requirements <sup>3</sup> (1) 25.2V 10.4 AH Lithium ion  7 lbs. 18 AH 5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger 2-amp, off-board  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Standard Electronics            | 50 amp, PG VSI                                |
| Battery Weight*  5.2 lbs. 10.4 AH Lithium ion (air safe travel battery)  Battery Charger  2-amp, off-board  Frame: 5-year limited  Drivetrain: 13-month  Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                 |                                               |
| Waranty  Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Battery Weight <sup>4</sup>     |                                               |
| Waranty  Drivetrain: 13-month  Electronics: 13-month                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Battery Charger                 | 2-amp, off-board                              |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Waranty                         | Drivetrain: 13-month<br>Electronics: 13-month |

- 1 Varies with userweight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- 2 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight ranacity.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 Battery weight may vary based on battery manufacturer.
- 5 Includes standard seat weight.
- 6 Power mobility device, not coded by dme pdac or does not meet criteria

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for power chair only. Overall measurements will vary based on seating and accessory selections.







**Note:** Transport of this item on commercial aircraft is subject to federal regulations and airline policy. Please consult your airline prior to your flight to ensure your Jazzy® Passport and its lithium ion battery are permitted.



(US) 800-800-8586 • (Canada) 888-570-1113 pridemobility.com

JAZZYPASSPORT\_042720





Experience the beauty of lightweight travel with the Jazzy® Passport! This compact power chair folds in just a few simple steps for effortless transport. With convenient storage the Jazzy Passport makes traveling a breeze.

- A compact and lightweight design
- Back seat pocket for extra storage while on the go
- Includes convenient, under seat mesh storage bag, mesh cup holder and 40" lap belt
- Large foot platform to accommodate the user's comfort
- Specialty foam seat design for extreme comfort
- Choice of 18 AH battery or 10.4 AH\* travel battery

## **Available Colors**



Black

## **Accessories**

• XLR USB charger

## **Military Patches**





\*Airline safe.