



FROM CATCHMENT AREA
 TO OVERFLOW/STORM
 8" INLET
 8" SMOOTHING INLET
 8" OVERFLOW DEVICE
 8" STUB OUT TO STORM DRAIN

WFF300 VORTEX FILTER WITH EXTENSION TUBE
 ULTRASONIC LEVEL SENSOR
 2" FLOATING FILTER
 SUBMERSIBLE PUMP IN COOLING JACKET
 NORMALLY OPEN FLOAT SWITCH FOR PUMP PROTECTION

DOMESTIC (CAN BE PLUMBED SEPARATE FROM FILTRATION SKID)
 RAINWATER FILTRATION SKID (SHOWN WITH DOMESTIC)
 DAY TANK
 BOOSTER PUMP SKID
 PRESSURE TANK
 TO END USE

SUBMERSIBLE PUMP WITH FILTRATION, DAY TANK, AND BOOSTER PUMP	ALL GRADES & ELEVATIONS TO BE SITE VERIFIED PRIOR TO CONSTRUCTION	DRAWN BY: CR 6/28/2018 CHECKED BY: BS 6/28/2018 NOT TO SCALE	REV 0
	DRAWING FOR ILLUSTRATIVE PURPOSES ONLY. NOT FOR CONSTRUCTION. DIMENSIONS AND LAYOUT SUBJECT TO CHANGE RAINWATER MANAGEMENT SOLUTIONS, 1-866-653-8337 WWW.RAINWATERMANAGEMENT.COM		