

# Vue 10.1" Capacitive Touch Display with BrightSign Built-in and Integrated LED Lights

MBS-1080C-POE-L



## 10.1" Capacitive Touch Display with BrightSign Built-In and Integrated LED Lights

Two trusted powerhouse digital signage leaders, Mimo Monitors and BrightSign, have teamed up to introduce the Mimo Vue with BrightSign Built-In Digital Signage Player. This display provides a fully encompassing, reliable, all-in-one digital signage solution that harnesses the power of the Mimo Vue technology and integrates the industry-leading BrightSign platform. The result is a high quality, easy-to-install digital signage solution that's immediately digital signage ready, making it extremely simple to use, especially for those already reliant on the BrightSign platform. Durable and instantaneously ready for commercial use. Featuring a modern zero bezel design and a bright, high contrast, IPS screen, this monitor is capable of providing a solution for any desired need.

The BrightSign Built-In Digital Signage Module is an HD Series 4 class BrightSign player. Built-in module is compatible with all BrightSign software, services, and supported CMS solutions.

### Features:

- IPS Screen with nearly 180 degree viewing angles
- LED Lights, great for indicating room availability
- HS124 - HD4 class BrightSign Built-in player
- HD class performance; runs BrightSign software or compatible CMS partners software
- H.265/H.264 video decode
- Video output up to 1080p60
- 10-bit video output (using H.265)
- Hardware accelerated HTML5 support
- Multi point capacitive touch screen
- Adjustable brightness
- Displays in either landscape or portrait orientations
- Fully compatible with Windows, Linux, and Mac OS

### Applications:

- Kiosk information system
- Gaming and entertainment
- Conference room scheduling
- POP/POS
- Elevator/ In-wall digital signage
- Interactive consumer engagement

### Product Specs

**Display Size**

10.1 inch

**Resolution**

1280 x 800

**Brightness**

350cd/m2

**Contrast Ratio**

800:1

**Connections**

Micro SD, USB, GPIO(x6), 3.5mm Audio, Ethernet

**Viewing Angle**

85/85/85/85

**Operating Temperature**

-10 to 50c

**Power Consumption**

24W

**Mount Pattern**

VESA-75mm

**Regulatory Certifications**

FCC, CE, ROHS