


# Myst Link 10.1" AV-over-IP Capacitive Touch Display, HDMI Capture

MY-1090CV



## Mimo Myst Link 10.1" AV-over-IP Touch Monitor With HDMI Capture Built-in

Designed to be a perfect conference room control interface, the Myst Link is the third generation of Mimo Monitors 10.1" monitor line. This innovative conference room solution is recognized by PCs as a regular display, maximizing usable space and productivity, without increasing complexity and IT requirements. Due to its cabling, which also supplies power (no power at the table needed!), it is seamless for IT to set up and simple to maintain, cutting long-term costs and the need for technical know-how. It also allows for long distance installations, paving the way for flexible and moveable furniture configurations, necessary for today's evolving work environment. In addition, the capacitive touch display provides a USB connection through to the host computer for connecting hardware such as a speaker/mic without requiring any additional extenders or cables. The Myst Link complies with Microsoft and Zoom specifications.

This HDMI capture capability allows your connected computer to stream high quality video up to 1080p video at 60 frames per second. The capture device converts video and audio from your HDMI source device into standard UVC and UAC. This video data stream can be presented to other displays or with video processing, sent over the internet to other online meeting participants, or many other options.

### Features:

- Multi-point capacitive touch screen
- HDMI capture
- Surface treatment: Hard coating (3H), anti-glare, anti-fingerprint
- Complies with Microsoft Teams and Zoom specifications
- Display has wide viewing angle, bright, sharp contrast and a high resolution IPS display
- Intergrated cable management
- Two audio paths for speakers and head phones
- Sensors include human presence temperature and orientation

### Applications:

- Conference room control
- Conference room scheduling
- Control interface where HDMI capture is needed

## Product Specs

### Display Size

10.1 inch

### Resolution

1280 x 800

### Brightness

400cd/m2

### Contrast Ratio

1000:1

### Connections

Cat5e Ethernet, USB through, HDMI

### Viewing Angle

85/85/85/85

### Operating Temperature

-10 to 40c

### Power Consumption

16W (total system)

### Mount Pattern

Desktop or Custom Wall Mount

### Regulatory Certifications

FCC, CE, ROHS, UL, RCM

### DISPLAY SECTION:

#### Video

AV-over-IP

#### External Power

Supplied AC/DC adapter or other 12V/3A source

#### Human Presence Sensor

IR. 3m at +/- 45 degrees

#### Other Sensors

- Ambient Light
- Orientation
- Temperature (2x)
- HID Compliant

#### Stereo Audio

200 Hz-20 kHz, 1W max

#### Headset

Stereo with mic and jack detect

#### Security Slot

Kensington lock port

#### Capture:

#### USB Video Class

UVC

#### USB Audio Class

UAC