JACK MASON


MIRABEAU

Racing Chronograph 40mm

JM-R402-004



Miyota Caliber No. 0S21 Chronograph Function



Setting The Time

- 1. Pull the crown out to the **2nd position**.
- 2. Turn the crown to set **Hour and Minute Hands**.
- 3. After the time has been set, push the crown back to **Normal position**.

Setting The Date

- 1. Pull the crown out to **1st position**.
- 2. Turn the crown counter-clockwise to set the date.
 - * Set the date between the hours of 2:00 am to 8:00 pm to ensure the date changes the following day.
- 3. After the date has been set, push the crown back to **Normal position**.

Using The Chronograph Function

This chronograph will measure and display time in 1/1 second units up to a maximum of 59 minutes 59 seconds.

Measuring time with a Chronograph:

- 1. The chronograph can be started and stopped each time **Button A** is pressed.
- 2. Pressing **Button B** resets the chronograph and the **Chronograph Second Hand** and **Chronograph Minute Hand** return to zero position.

Chronograph Reset

This Procedure should be performed when the **Chronograph Second Hand** does not return to zero position after the chronograph has been reset, and including after the battery has been replaced.

- 1. Pull the crown to the **2nd Position**.
- 2. Press **Button A** to set the chronograph second hand to the zero position. The chronograph hand can be advanced rapidly by continuously pressing **Button A**.
- Once the hand have been reset to the zero position, return the crown to Normal Position.

*Do not push crown to **Normal Position** while the **Chronograph Second Hand** returns to zero position. It stops on the way when crown are returned to **Normal Position** and its position is recognized as zero position.