



BrandBold Concrete

ULTRA SEAL 5000

STEP 4

TOOLS & MATERIALS REQUIRED FOR STEP 4

- Lint resistant 3/8" nap
- (Optional: Solvent resistant sprayer)

DESCRIPTION

BrandBold Brilliance Concrete **ULTRA SEAL 5000** is a tough, acrylic concrete sealer in a solvent base. It is designed to protect and beautify all types of concrete with a high gloss durable clear coating. **ULTRA SEAL 5000** is non-yellowing to preserve the appearance of all types of decorative concrete.

FEATURES

- High Gloss
- Durable
- U.V. Resistant
- Non-Yellowing

SURFACE PREPARATION

Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or similar solvent-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete with BrandBold Brilliance Concrete **NEUTRALIZER & DEGREASER**. Use a bristle brush for heavily oiled spots. If surface is slick, etch with BrandBold Brilliance Concrete **ETCH & CLEAN**. Apply only when surface and air temperatures are above 50° F and below 100° F. Do not apply to excessively hot surfaces, as rapid drying may cause bubbles to form.

APPLICATION

Apply evenly. Brush may be used where roller won't reach. Wait until the surface is tack-free before applying a second coat. Apply perpendicular to the first coat. Cross-rolling allows for an even application. If spraying, use a solvent resistant sprayer holding tip no more than 8" from surface during application. Back rolling is recommended while spraying. Clean up with Xylene. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Cooler temperatures or increased humidity will slow the dry time.

DO NOT THIN.

NET COVERAGE RATE

150-200 SqFt/gallon. Two thin coats are recommended for best results.

CLEANUP

Clean tools with Acetone or Xylene.

MAINTENANCE

Clean sealed surface with water only. Reseal surface as needed but no more than every two years to prevent buildup of sealer.



PROUDLY MADE IN THE USA

BrandBold Concrete

5017 Sirius Lane Charlotte, NC 28208 | www.brandboldconcrete.com



BrandBold® Concrete

ULTRA SEAL 5000 STEP 4

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Money-Back Guarantee only applies to customers that follow the BrandBold Concrete “Step” program and purchase all items and materials from BrandBold Concrete. Manufacturer retains the right to venue. SDS is available for all BrandBold products upon request.



PROUDLY MADE IN THE USA

BrandBold Concrete

5017 Sirius Lane Charlotte, NC 28208 | www.brandboldconcrete.com