

CONTAINERISED SELF BUNDED TANK RANGE



SUITABLE FOR THE STORAGE AND DISPENSING OF DIESEL, LUBRICANTS, KEROSENE AND PETROL.

- Integrated Bunded Pump Bay and Tank Access Platform design providing access to the full tank functionality in one convenient location on the tank.
- Unique rounded rectangular tank profile maximises the storage capacity of the tank and provides the strength of a cylindrical design.
- Rounded roof profile that will not pool water / snow or sand.
- CSC plated as 10ft / 20ft / 40ft / 48ft Standard Container.
- Dispensing Equipment housed within a lockable bunded pump bay housing.
- Lockable Container Doors with option for Roller Door.
- Supplied with Interstitial Emergency Relief Vent that will relieve the gap between the two tanks in the event of a fire.
- DN80 Fill Point c/w Camlock Male Fitting / Dust Cap / Fire Safe Full Bore Ball Valve / Wafer Style Non Return Valve.
- DN80 Suction Outlet c/w Anti Syphon Valve and Two Piece Full Bore Fire Safe Ball Valve.
- DN80 Mechanical Overfill Valve + 12V Battery Operated Overfill Alarm. 2 x 600mm manways with integrated tank access ladder assembly.
- Fold out AS1657 designed and approved access ladder.
- Removable plate to allow the linking of multiple tanks in tank farm applications. Full under tank visibility allows for regular visual inspection of the tank base and prevents the base rusting by providing unrestricted air flow under the tank.
- Paint Colour RAL9003 Signal White. Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process.
- Primer Hemptadur 1530. 2nd Coat Hemptadur Hi-Build 4520. Final Coat Hemptadur Enamel 55100. Finished dry film thickness no less than 180 um.
- Supplied with all required statutory safety decals for your region of operation.



PRODUCT RANGE

	CON-12	CON-18	CON-30	CON-38	CON-69	CON-75	CON-80	CON-110
Capacity	12000L	18000L	30000L	38000L	69000L	75000L	80000L	110000L
Safe Fill Level	10100L	16250L	27000L	33500L	65000L	71500L	76000L	106500L
Length (mm)	3000	3000	6058	6058	12192	12192	14630	14630
Width (mm)	2438	2438	2438	2438	2438	2438	2438	3000
Height (mm)	2896	2896	2896	2896	2896	2896	2896	3200
Weight (kg)	450	450	7500	7500	14500	14500	15925	21100
Container Footprint	10FT High	10FT High	20FT High	20FT High	40FT High	40FT High	48FT High	Break Bulk
Integrated Pump Bay	Yes	No	Yes	No	Yes	No	Yes	Yes