

STORE

SELF BUNDED TANK RANGE



SUITABLE FOR THE STORAGE & DISPENSING OF DIESEL, PETROL, KEROSENE, LUBRICANTS & WASTE OIL. AN INNOVATIVE NEW RANGE OF TANKS, THEY ARE PERFECT FOR HOME BASE REFUELLING APPLICATIONS WITH LOCKABLE FULL HEIGHT PUMP BAY HOUSING FOR SECURE STORAGE OF DISPENSING EQUIPMENT.

- Galvanised grated bunded area with drain.
- DN50 (2") Flanged 150# Fill Point with Full Bore Ball Valve / Non Return Valve / Male Camlock Fitting / Dust Cap / Mechanical Over II Protection Valve and 12V Over II Alarm.
- DN50 (2") Flanged 150# Suction Point with Anti Syphon / Foot Valve Assembly.
- Spare DN25 (1") Suction Outlet.
- SPARE FITTINGS - Numerous spare fittings on top of the tank for retrofitting of instrumentation or other devices.
- 600mm dia manway with internal ladder.
- Calibrated anodised aluminium dipstick with brass lockable dip stick cover fitting.
- Anodised aluminium interstitial dipstick with brass lockable dip stick cover fitting.
- Interstitial emergency vent.
- Primary tank free air vent.
- DECALS - Statutory safety decals.
- Forklift tynes have been incorporated in the front / rear of the tank to facilitate loading and positioning on site.
- Certified crane lifting lugs have been incorporated to facilitate crane loading and positioning on site. The lifting lugs are NOT certified to lift the tank with fuel.
- Letterbox style secure weatherproof hose inlet / outlet assembly.
- Paint Colour RAL9003 Signal White / Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur Hi-Build 4520. Final Coat Hempathane Enamel 55100 Finished dry film thickness no less than 180 um.



PRODUCT RANGE

	STORE-2.5	STORE-5.5	STORE-11	STORE-16	STORE-22
Capacity	2500L	5000L	11000L	16000L	22000L
Safe Fill Level	2250L	5000L	10000L	15000L	20000L
Length (mm)	2500	2950	2950	3950	4950
Width (mm)	1140	1140	2300	2300	2300
Height (mm)	1500	2550	2550	2550	2550