



Instruction manual

## **GT RAPIDFLO** HI-FLOW FUEL PUMP (GT-01)

10 Year Warranty \*conditions apply

## **PRODUCT OVERVIEW FEATURES & BENEFITS** The GT RAPIDFLO<sup>™</sup> is a rotary action pump suitable for transferring diesel, ULP, aviation fuels, kerosene & light oils (up to SAE30). Lockable Handle Nozzle Holder To Prevent Spillage To prevent theft of fluid Allows nozzle to be fixed in non-siphoning position The RAPIDFLO<sup>™</sup> is capable of Anti-kink Springs transfer rates of 800ml per revolution 2" Sliding Bung Adaptor Prevents hose from (up to 100L/min depending on restricting fluid delivery Suits different height drums from 60L - 205L viscosity) from 60 - 205L drums and Rotary Action tanks. Quick, effortless delivery of fluids in both directions The RAPIDFLO<sup>™</sup> is also suitable for **Delivers 800ml Per Revolution** users who either cannot use an Able to achieve flow rates electric fuel pump for safety reasons up to 100L/min or do not have access to power in remote locations. 2.4m Anti-static Rubber Hose It can be used to transfer AV-Gas\* Three Piece Suction Tube Safely transfer gasolene Allows length of suction tube to and kerosene and Jet A1\* although users of aviation be adjusted to accommodate different height drums fuels must check material compatibility with the fuel product they are using. Steel Construction & Fully Repairable Provides a much longer service life **TECHNICAL SPECIFICATIONS OPTIONAL ACCESSORIES PACKAGE INCLUDES** Suitable for 60L - 205L drums GT RAPIDFLO™ pump 2.4m anti-static rubber delivery hose 3 piece suction tube Built-in 2" sliding bung adaptor

Delivers 800ml per revolution (Up to 100L/min) 2.4m anti-static rubber delivery hose 2" sliding bung adaptor Three piece suction tube Suitable for use with petrol, diesel, kerosene, lubricating oils (up to SAE 30) and some aviation fuels Wetted Components: Aluminium, Steel, zinc, nitrile rubber, viton

