

Ultra Slim LED Floodlight

USER MANUAL



Ultra Slim LED Floodlight User Manual

Important Information:

These instructions contain safety information, read, and follow them carefully. We will not accept any responsibility for injury, damage or loss which may occur due to incorrect installation, operation, or maintenance.

Warning:

To avoid the risk of fire, explosion, or electric shock, this product should be installed, inspected, and maintained by a qualified electrician only, in accordance with all applicable electrical codes.

Safety Instructions:

- Be certain electrical power is OFF before and during installation and maintenance.
- Make sure the supply voltage is the same as the rated luminaire voltage.
- Changes to the design and modifications to the luminaire are not permitted.
- Observe the national electrical safety rules and regulations during installation.

Specifications:

- Material: ADC#12 Aluminum
- Input Voltage: AC220-240V
- Lumen: 90-100Lms/W
- Beam Angle: 90°
- Colour Temperature: 6000K
- CRI: Ra>80
- PF: >0.9
- IP Rating: IP65
- Cable Length: Rubber wire 1mt 3G1.0mm²

Dimensions:

Model	Dimension (L*W*H)
IK03-E-30W	169.5x154x31.3mm
IK03-E-50W	205.3x182.8x31.7mm
IK03-E-100W	243.8x216.5x33mm
IK03-E-200W	318x283.7x33mm
IK03-E-300W	352.5x322.9x45mm
IK03-E-400W	407x370x45mm
IK03-E-500W	465.5x419.9x48.2mm

Installation Diagram:

