



Urban Restoration Group US, Inc.
5439 San Fernando Rd W
Los Angeles, CA 90039, USA
Web: www.graffitiremovalinc.com
Email: sales@graffitiremovalinc.com
Tel: (818) 247-2555
Fax: (818) 247-2515

TECHNICAL DATA SHEET

Acetone Technical

PARAMETER	UNIT	SPECIFICATION
Appearance	Visual	Pass
Assay	Wt. %	99.5 Min
Color	APHA	5 Max
Acidity (as Acetic Acid)	Wt. %	0.002 Max
Alkalinity (as Ammonia)	Wt. %	0.001 Max
Specific Gravity @ 25°C		0.7910 – 0.7930
Distillation Range, 1°C including 56.1°C		1
Permanganate Time @ 25°C	Minutes	30 Min
Non-Volatiles Matter	Ppm	5 Max
Water	Wt. %	0.5 Max
Water Miscibility		Pass
Odor		Non-Residual

Material meets ASTM-329 Specification

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (818) 247-2555 or visit us at www.graffitiremovalinc.com.