

Rating Sheet
Emergent Coils, LLC ~ 855-264-5669

sales@emergentcoils.com

5W30X33-610-HRD

No. Coils:	1	Coil Type:	Water - Cooling
Fin Height (In.):	30	Fin Mat./Thickness/Type:	Aluminum/ 0.006/ Waffle
Fin Length (In.):	33	Tube Mat./Wall/OD:	Copper/ 0.020/ 5/8 Inch
Air Flow/Coil (ACFM/SCFM)	3503 / 3438 (S)	Tube Spacing:	1.5 x 1.299
ACFM/SCFM Velocity (fpm):	509.5 / 500.1	Tube Surface:	Smooth
EDB/EWB (°F):	80 / 67	Casing Material:	Galv
EWT (°F):	45	Fluid Type:	Water
Fluid Temp. Drop (°F):	10	FF Inside*:	0
Rows/FPI:	6/10	FF Outside*:	0

	Per Coil	Total All Coils
LDB/LWB (°F):	55.1 / 54.7	
Total Heat (BTUH):	129,996	129,996
Sensible. Heat (BTUH):	93,166	93,166
LWT (°F):	55.0	
Fluid Flow (GPM):	25.9	25.9
Fluid Press. Drop (Feet):	5.98	
Tube Velocity (fps):	2.84	
Reynolds number:	10,265.22	
Air Pressure Drop (in W.G.):	0.74	
Connection Size (In.):	1.5	
Approximate Fluid Volume (Gal) :	6.2	6.2
Uncrated, Dry Coil Weight: 139.5		

Printed on 6/26/2018 using Total Package II; program version 1.2.2018.1 - DLL/Data 1.0.5.68/20170829.1

* (Hr*ft²*°F/Btu) Fouling Factor Units

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.