

Rating Sheet

**Emergent Coils, LLC ~ 855-264-5669**

sales@emergentcoils.com

**5W30X69-610-TRE**

No. Coils:	1	Coil Type:	Water - Cooling
Fin Height (In.):	30	Fin Mat./Thickness/Type:	Aluminum/ 0.006/ Waffle
Fin Length (In.):	69	Tube Mat./Wall/OD:	Copper/ 0.020/ 5/8 Inch
Air Flow/Coil (ACFM/SCFM)	7324 / 7188 (S)	Tube Spacing:	1.5 x 1.299
ACFM/SCFM Velocity (fpm):	509.5 / 500	Tube Surface:	Smooth
EDB/EWB (°F):	80 / 67	Casing Material:	Galv
EWT (°F):	45	Fluid Type:	Water
Fluid Temp. Drop (°F):	10	FF Inside*:	0
Rows/FPI:	6/10	FF Outside*:	0

	<b>Per Coil</b>	<b>Total All Coils</b>
LDB/LWB (°F):	54.1 / 53.8	
Total Heat (BTUH):	288,818	288,818
Sensible. Heat (BTUH):	201,891	201,891
LWT (°F):	55.0	
Fluid Flow (GPM):	57.6	57.6
Fluid Press. Drop (Feet):	12.23	
Tube Velocity (fps):	4.20	
Reynolds number:	15,213.31	
Air Pressure Drop (in W.G.):	0.76	
Connection Size (In.):	2	
Approximate Fluid Volume (Gal) :	12.1	12.1
Uncrated, Dry Coil Weight: 258.2		

Printed on 6/28/2018 using Total Package II; program version 1.2.2018.1 - DLL/Data 1.0.5.68/20170829.1

\* (Hr\*ft<sup>2</sup>\*°F/Btu) Fouling Factor Units

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.