

Rating Sheet

Emergent Coils, LLC ~ 855-264-5669

sales@emergentcoils.com

5W30X78-610-FRE

No. Coils:	1	Coil Type:	Water - Cooling
Fin Height (In.):	30	Fin Mat./Thickness/Type:	Aluminum/ 0.006/ Waffle
Fin Length (In.):	78	Tube Mat./Wall/OD:	Copper/ 0.020/ 5/8 Inch
Air Flow/Coil (ACFM/SCFM)	8278 / 8125 (S)	Tube Spacing:	1.5 x 1.299
ACFM/SCFM Velocity (fpm):	509.4 / 500	Tube Surface:	Smooth
EDB/EWB (°F):	80 / 67	Casing Material:	Galv
EWT (°F):	45	Fluid Type:	Water
Fluid Temp. Drop (°F):	10	FF Inside*:	0
Rows/FPI:	6/10	FF Outside*:	0

	Per Coil	Total All Coils
LDB/LWB (°F):	54.6 / 54.2	
Total Heat (BTUH):	317,651	317,651
Sensible. Heat (BTUH):	224,524	224,524
LWT (°F):	55.0	
Fluid Flow (GPM):	63.4	63.4
Fluid Press. Drop (Feet):	8.92	
Tube Velocity (fps):	3.47	
Reynolds number:	12,539.96	
Air Pressure Drop (in W.G.):	0.75	
Connection Size (In.):	2	
Approximate Fluid Volume (Gal) :	13.6	13.6
Uncrated, Dry Coil Weight: 294.7		

Printed on 6/28/2018 using Total Package II; program version 1.2.2018.1 - DLL/Data 1.0.5.68/20170829.1

* (Hr*ft²*°F/Btu) Fouling Factor Units

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.