

NATIONAL-SPENCER, INC.

ZEE LINE LUBRICATION EQUIPMENT

Phone 800-231-1525

Fax 800-637-9511

Web Address www.zeeline.com

Part # 1213A

Air Operated Chassis Lube System

Features

- ❖ Heavy-duty 55:1 ratio
- ❖ Air pressure 70-100 PSI
- ❖ Air consumption 5.50 CFM
- ❖ Air inlet ¼" NPT
- ❖ Grease outlet ¼" NPT
- ❖ ¼" x 6' grease hose (1806)
- ❖ ¼" x 48" air hose
- ❖ Foot valve
- ❖ Air filter with auto water drain, regulator, gauge, ball valve and quick disconnects (1559A-ASSY)
- ❖ Fits 120 lb. drum
- ❖ Tube length 29 ½"
- ❖ Drum adapter 2" NPT 1 5/32" tall
- ❖ Pump tube diameter 1 5/32"
- ❖ Approximate capacity
2.2 lbs./min free flow with 100 psi
air pressure and grease at 68° F
1.3 lbs./min through 33 feet of ¼"
hose and grease control handle

Recommended for

- ✓ Greases through NLGI #2

Application

- Automotive
- Industrial
- Agriculture

Number of boxes and contents

- ❑ 1 box (22" x 48" x 5 ½") containing all products (38 lb.).
- ❑ UPC Code 0 1595441223 6

Complete system
with all parts shown
for pumping grease
from 120-lb. drum



Control
Handle
1536A




"Z" Swivel
1545



Regulator
Combination
Unit
1559A-ASSY



Drum Cover
680-823



Follower
Plate
1524



Drum Dolly
120-S

1213AAR
Pump ONLY
no accessories