

NATIONAL-SPENCER, INC.

ZEE LINE LUBRICATION EQUIPMENT

Phone 800-231-1525

Fax 800-637-9511

Web Address www.zeeline.com



1514 Series Mechanical Meter with Strainer

Specifications

Applications: Designed for outdoor, year-round use on fuel transfer pumps in the 4 to 20 GPM flow range. Factory calibrated for use with gasoline, diesel fuel or kerosene.

	Gallon Model 1514	Liter Model 1514L
Unit of Measure:	U.S. Gallon	Liter
Flow Range:	4 to 20 GPM	15 to 75 LPM
Accuracy:		
Factory Calibration:	$\pm 2\%$	$\pm 2\%$
(Accuracy is Factory Calibrated with diesel fuel. Field calibration available on all models.)		
Design Type:	Nutating Disc	Nutating Disc
Housing:	Aluminum	Aluminum
Max. Working Pressure:	50 PSIG	3.4 bar
Inlet/Outlet:	$\frac{3}{4}$ " or 1"	$\frac{3}{4}$ " or 1"
Threads:	NPT	NPT or BSPP
Maximum Batch Total:	999.9	9,999
Maximum Cumulative Total:	99,999	999,999
Dimensions:		
Width:	5.5 inches	13.9 cm
Height:	4.5 inches	11.4 cm
Depth:	5.5 inches	13.9 cm
Shipping Weight:	4 lbs.	1.8 kg

All models with NPT threads are UL Listed

- Durable aluminum housing.
- Mechanical design for easy use and service.
- Easy-to-read mechanical display.
- Built-in strainer
- Field and Factory Calibration.