

NATIONAL-SPENCER, INC.

ZEE LINE LUBRICATION EQUIPMENT

Phone 800-231-1525

Fax 800-637-9511

Web Address www.zeeline.com

Part # 3574A

Air Operated Chassis Lube System

Features

- ❖ Heavy-duty 55:1 ratio
- ❖ Air pressure 70-100 PSI
- ❖ Air consumption 5.50 CFM
- ❖ Air inlet ¼" NPT
- ❖ Grease outlet ¼" NPT
- ❖ ¼" x 6' grease hose
- ❖ ¼" x 48" air hose
- ❖ Air regulator with gauge, filter and automatic water drain
- ❖ Quick connect couplers for air
- ❖ Foot valve
- ❖ Ball valve
- ❖ Fits 35-50 lb. pail
- ❖ Tube length 17 ¾"
- ❖ Drum adapter 2" NPT 1 5/32" tall
- ❖ Pump tube diameter 1 5/32"
- ❖ Approximate capacity
2.2 lbs./min free flow with 100 psi
air pressure and grease at 68° F
1.3 lbs./min through 33 feet of ¼"
hose and grease control handle

Recommended for

- ✓ Grease through NLPI #2

Application

- Automotive
- Industrial
- Agriculture

Number of boxes and contents

- 1 box (19" x 34" x 4 ½") containing all products (24 lb.).
- UPC Code 0 1595443577 8

Portable style
complete system
with all parts shown
for pumping grease
from 35-50 lb. pail



3574AAR
Pump ONLY
no accessories




**Control
Handle
1536A**



**Air Filter,
Regulator,
Gauge Pkg.
1559A-ASSY**



**Drum Cover
18527**



**Follower
Plate
107016**



**"Z" Swivel
1545**