# NATIONAL-SPENCER, INC.

### ZEE LINE LUBRICATION EQUIPMENT

Phone 800-231-1525

Fax 800-637-9511

Web Address www.zeeline.com



### Features

- Dual voltage 12DC and 24DC
- Output flow rate 8 to 10.5 GPM
- ✤ Inlet port ¾" barbed
- Outlet port ¾" barbed
- Lightweight and compact
- Includes battery cables
- Includes battery clips
- Suction hose not included
- Rapid transfer of high viscosity fluids
- Built in bypass valve and on/off switch
- Self-priming, positive displacement

### **Recommended for**

- ✓ Kerosene
- ✓ Diesel fuel
- ✓ Antifreeze
- ✓ Hydraulic fluid
- X CAUTION: Not for use with gasoline or flam

## <u>Part #924</u>

Portable Electric Transfer Pump

For transferring kerosene, diesel fuel, antifreeze and hydraulic fluid

### ▲ Safety Instructions

To ensure safe and efficient operation, it is essential to read and follow each of these warnings and precautions.

- 1. Improper use or installation of this product can cause serious bodily injury or death.
- 2. Do NOT smoke near pump or use pump near an open flame. Fire could result.
- 3. This product should not be used for fluid transfer into aircraft.
- 4. This product is not suited for use with medical products, water, or fluids for human consumption.
- 5. Tank or barrel should be anchored to prevent tipping in the full and empty conditions.
- 6. Motor is NOT explosion proof. Do not use within 20 ft. of a hazardous location where explosive vapors may be present. Explosion and death could result.

### Application

> Applications where rapid transfer of low viscosity fluid (10 wt. or lighter) is desired

### Number of boxes and contents

- □ 1 box (16" x 16" x 9") (16 lb.)
- □ UPC Code 0 1595440924 3