## SAFETY DATA SHEET

Safety Data Sheet according to regulation (EC) No 1907/2006 & 1272/2008 and amendments

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

Product Identifier: SOLAREZ® FLY TIE THICK HARD Product Description: Aliphatic urethane mixture - UV Cure

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST.

Intended/Recommended Use: Radiation cured coating.

**DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET** 

Company: WAHOO INTERNATIONAL, INC. 1315 Hot Springs Way #106 Vista, CA 92081 USA

Outside USA call +1-760-476-3559 fax +1 760 476-0146

Email: solartech@solarez.com

**EMERGENCY PHONE** 

800 875-3833

® indicates trademark registered in the U.S. Outside the U.S., mark may be registered, pending or a trademark. Mark is or may be used under license.

## 2. HAZARDS IDENTIFICATION

Irritating to eyes and skin.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component / CAS No.	%	EC-No	REACH Registration Number	Classification	Classification according to Regulation (EC) No 1272/2008 (CLP)
Aliphatic Urethane Methacrylate	78 - 100	-	Not available		
Isobornyl Acrylate 5888-33-5	5-10	201-039-8	Not available	Xi; R36/38 Xn; R48/22 N; R50/53	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)
Initiator	<1	210-0NA37-6	Not available	Xi; R36/38 Xn; R48/22	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)

## 4. FIRST AID MEASURES

# **DESCRIPTION OF FIRST AID MEASURES**

**Eye Contact:** 

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

## **Skin Contact:**

Remove contaminated clothing and shoes without delay. Wash immediately with plenty of water. Do not reuse contaminated clothing without laundering. Get medical attention if pain or irritation persists after washing or if signs and symptoms of overexposure appear.

# Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

## Inhalation:

Material is not expected to be harmful if inhaled. Remove to fresh air.

#### MOST IMPORTANT SYMPTOMS AND EFFECTS.

## INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDS

#### **General Information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

## 5. FIRE-FIGHTING MEASURES

## **EXTINGUISHING MEDIA**

## Suitable Extinguishing Media:

Use water spray or fog, carbon dioxide or dry chemical.

## **Extinguishing Media to Avoid:**

high pressure water jet.

#### SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Keep containers cool by spraying with water if exposed to fire.

#### ADVICE FOR FIREFIGHTERS

## **Protective Equipment:**

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See MSDS Section 8 (Exposure Controls/Personal Protection).

\_\_\_\_\_

## 6. ACCIDENTAL RELEASE MEASURES

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

## **Environmental Precautions:**

None known

## Methods and material for containment and cleaning up:

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

#### References to other sections:

See Sections 8 and 13 for additional information.

.....

## 7. HANDLING AND STORAGE

## PRECAUTIONS FOR SAFE HANDLING

**Precautionary Measures:** Avoid contact with eyes, skin and clothing. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Keep container tightly closed. Wash thoroughly after handling.

Special Handling Statements: Provide good ventilation of working area (local exhaust ventilation if necessary).

## Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight.

Storage Temperature: Store at 4 - 40 °C

Reason: Quality.

VCI Storage Class: 10

Specific end use(s): Composite field repair.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**CONTROL PARAMETERS** 

77-58-7 Dibutyltin dilaurate

United Kingdom: WEL (Workplace Exposure Limits) 0.1 mg/m<sub>3</sub> (TWA) Europe ILV (Indicative Limit Values): Not established

\_\_\_\_\_\_

# 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

**Colour:** colorless to straw **Appearance:** clear viscous liquid

Odor:acrylateBoiling Point:>100 °CMelting Point:Not available

Vapor Pressure: <0.013 hPa @ 20 °C

Specific Gravity/Density: 1.05

Vapour density: Not available Percent Volatile (% by wt.): Not available Solids Content: >=99% :Ha Not available Saturation In Air (% By Vol.): Not available **Evaporation Rate:** Not available Solubility In Water: slightly soluble Acid Number (mg KOH/g): Not available Hydroxyl Value (mg KOH/g): Not available

Volatile Organic Content(1999/13/EC): Not available Flash point: >100 °C Setaflash Flammable Limits (% By Vol): Not available Autoignition temperature: Not available Decomposition Temperature: Not available

Partition coefficient (noctanol/

water): Not available
Fat Solubility (Solvent-Oil): Not available
Viscosity (Kinematic): Not available

Viscosity (Dynamic): 6000 - 9000 mPa.s @ 25 °C

# 10. STABILITY AND REACTIVITY

Reactivity: No information available

CHEMICAL STABILITY

Stability: Stable

Conditions To Avoid: Avoid direct exposure to sunlight. Avoid temperatures above 60°C (140°F). Avoid

friction with temperature increase as result. Avoid exposure to strong UV sources.

Loss of dissolved air. Loss of polymerization inhibitor. Avoid direct contact with heat sources.

#### POSSIBILITY OF HAZARDOUS REACTIONS

Polymerization: May occur

**Conditions To Avoid:** Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers. Hazardous polymerization can occur when exposed to direct sunlight. Hazardous exothermic polymerization can occur when heated. Avoid contact with bases or amines. Avoid contact with strong oxidizing agents. Avoid contact with free radical initiators.

**Incompatible materials:** Avoid contact with peroxides. Copper, copper alloys, carbon steel, iron and rust. Avoid free radical producing initiators. Contact with alkalis. They give an exothermic reaction with the product. Unintentional contact with them should be avoided. Avoid contact with active metals. Hazardous polymerization may occur.

**Hazardous Decomposition** 

**Products:** 

oxides of carbon

smoke

hydrocarbons

soot

# 11. TOXICOLOGICAL INFORMATION

## INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Eyes, Skin, Oral.

**Acute toxicity - oral:** Not classified - Based on available data and/or professional judgment, the classification criteria are not met.

Acute toxicity - dermal: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - inhalation:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin corrosion / irritation:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Serious eye damage / eye irritation: Causes serious eye irritation.

**Respiratory sensitization:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin sensitization:** May cause an allergic skin reaction.

**Carcinogenicity:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Germ cell mutagenicity:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Reproductive toxicity:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure:** Not Classified. **-** Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - repeated exposure:** Not Classified. **-** Based on available data and/or professional judgment, the classification criteria are not met.

**Aspiration hazard:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

## PRODUCT TOXICITY INFORMATION

## **ACUTE TOXICITY DATA**

#### **LOCAL EFFECTS ON SKIN AND EYE**

Acute Irritation eye irritating (tested)
Acute Irritation dermal Not irritating

## **ALLERGIC SENSITIZATION**

Sensitization respiratory No data Sensitization Skin Sensitizing

#### **GENOTOXICITY**

## Assays for Gene Mutations

Ames Salmonella Assay No data

# OTHER INFORMATION

The toxicity data above are the results from Cytec sponsored studies or from the available public literature.

The toxicological properties of this material have not been fully determined.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

#### HAZARDOUS INGREDIENT TOXICITY DATA

#### **ACUTE TOXICITY DATA**

Dibutyltin dilaurate

oral (gavage) rat Acute LD50 (Actual) 175 mg/kg dermal rabbit Acute LD50 (Actual) ~ 6800 mg/kg

Triphenylstibine

oral (gavage) rat Acute LD50 (Actual) < 100 mg/kg dermal rabbit Acute LD50 (Actual) > 200 mg/kg

## **LOCAL EFFECTS ON SKIN AND EYE**

Acrylated resin
Acute Eye Irritation rabbit irritating
Acute Dermal Irritation rabbit Irritating

# 12. ECOLOGICAL INFORMATION

## 13. DISPOSAL CONSIDERATIONS

# **Waste Treatment Methods**

The Company encourages the recycle, recovery and reuse of materials, where permitted. If disposal is necessary, The Company recommends that organic materials, especially when classified as hazardous waste, be disposed of by thermal treatment or incineration at approved facilities. All local and national regulations should be followed.

# 14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements. ADR/RID/ADN

Dangerous Goods? Not applicable/Not regulated IMO

Dangerous Goods? Not applicable/Not regulated

ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

## 15. REGULATORY INFORMATION

## LABELING ACCORDING TO EC DIRECTIVES

Symbol(s): Xi – Irritant

#### Risk Phrases:

R36/38 - Irritating to eyes and skin.

## Safety Phrases:

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 - After contact with skin, wash immediately with plenty of soap and water.

#### **HAZARDOUS INGREDIENTS**

No Hazardous Ingredients for Label

## SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS / LEGISLATION SPECIFIC FOR THE SUBSTANCE OR **MIXTURE**

Ozone Depleting Substances (Regulation (EC) No 1005/2009): Not applicable Persistent Organic Pollutants (Regulation (EC) No 850/2004): Not applicable

Substances subject to Authorization (Annex XIV of Regulation (EC) No 1907/2006): Not applicable

Water Endangering Class (Germany): 2 according to VwVwS, 17.05.1999

## **Inventory Information**

## United States (USA):

All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

#### Canada:

All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

Australia: All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on AICS.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS) inventory or are not required to be Listed on the Japanese inventory.

**Korea:** All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory.

**Philippines:** All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine inventory.

\_\_\_\_\_\_

# 16. OTHER INFORMATION

Reasons for Issue: New Format

Classification methods include one or more of the following: use of specific product data, read-across data, modeling, professional judgment or a component based evaluation.

## **Component Risk and Hazard Phrases**

Acrylated resin

R36/38 - Irritating to eyes and skin.

Dibutyltin dilaurate

R36/38 - Irritating to eyes and skin.

R48/22 - Harmful: danger of serious damage to health by prolonged exposure if swallowed.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Triphenvlstibine

R20/22 - Harmful by inhalation and if swallowed. H302 - Harmful if swallowed.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.