

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

GYEON Q2 CanCoat EVO

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Vehicle protective product - ceramic coating designed for paintwork
Enthusiasts and professional use (End consumer)

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	Gyeon Technology	
Street:	1405-538, 212, Gasan digital 1-ro	
Place:	Geumcheon-gu, Seoul, Korea	
Telephone:	+82-10-4339-3599	
Contact person:	Robert Gyeon	
e-mail:	sales@gyeonquartz.com	
Responsible Department:	Dr. Gans-Eichler	e-mail: info@tge-consult.de
	Chemieberatung GmbH	Tel.: +49(0)2534 6441185
	Otto-Hahn-Str. 36	www.tge-consult.de
	D-48161 Münster	

Supplier

Company name:	Gyeon UK Ltd	
Street:	20 Crichtiebank Business Centre, Mill Road	
Place:	GB-AB51 5NQ Inverurie	
e-mail:	hello@gyeonquartz.uk	
Contact person:	Richard Cooper	Telephone: +44 (0)7984 056790

1.4. Emergency telephone number:

+82-10-4339-3599

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**GB CLP Regulation**

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 2 of 17

Hazard components for labelling

Naphtha (petroleum), light alkylate; Low boiling point modified naphtha
Distillates (petroleum), hydro-treated light; Kerosine - unspecified
stoddard solvent; Low boiling point naphtha - unspecified
toluene

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.
Refer to chapter 3.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 3 of 17

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
541-02-6	Decamethylcyclopentasiloxane			30 - < 35 %
	208-764-9			
64741-66-8	Naphtha (petroleum), light alkylate; Low boiling point modified naphtha			10 - < 12 %
	265-068-8	649-276-00-X		
	Asp. Tox. 1; H304			
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified			10 - < 12 %
	265-149-8	649-422-00-2		
	Asp. Tox. 1; H304			
8052-41-3	stoddard solvent; Low boiling point naphtha - unspecified			5 - < 7 %
	232-489-3	649-345-00-4		
	Flam. Liq. 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H372 H304 H411			
108-88-3	toluene			1 - < 3 %
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			
546-68-9	Titanium tetraisopropanolate			1 - < 3 %
	208-909-6			
	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3; H226 H319 H336			
107-46-0	Hexamethyldisiloxane			1 - < 3 %
	203-492-7			
	Flam. Liq. 2, Aquatic Acute 1, Aquatic Chronic 2; H225 H400 H411			
67-56-1	methanol			0.2 - < 0.3 %
	200-659-6	603-001-00-X		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
541-02-6	208-764-9	Decamethylcyclopentasiloxane	30 - < 35 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
64742-47-8	265-149-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified	10 - < 12 %
	inhalation: LC50 = > 5,3 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
108-88-3	203-625-9	toluene	1 - < 3 %
	inhalation: LC50 = (28,1) mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
67-56-1	200-659-6	methanol	0.2 - < 0.3 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		

Further Information

- Naphtha (petroleum), light alkylate; Low boiling point modified naphtha (P)

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 4 of 17

- stoddard solvent; Low boiling point naphtha - unspecified (P)

Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7).

This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.: Decamethylcyclopentasiloxane (CAS: 541-02-6; 20.06.2018)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Observe risk of aspiration if vomiting occurs. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation can cause damage to the respiratory tract or lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. alcohol resistant foam.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 5 of 17

General measures

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Remove persons to safety. Remove all sources of ignition. Ventilate affected area.

Wear personal protection equipment. (See section 8.)

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.

Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 6 of 17

peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Skin protection

Wear fire/flame resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 7 of 17

Insufficient ventilation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid.
 Colour: clear
 Odour: Petroleum

Changes in the physical state

Melting point/freezing point: not determined
 Boiling point or initial boiling point and boiling range: 104 °C
 Flash point: 15 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: not determined
 Upper explosion limits: not determined
 Auto-ignition temperature: not determined
 Decomposition temperature: not determined

Oxidizing properties

none.

pH-Value: not determined
 Viscosity / dynamic: not determined
 (at 40 °C)
 Viscosity / kinematic: not determined
 (at 20 °C)
 Flow time: not determined
 Water solubility: not miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: SECTION 12: Ecological information
 Vapour pressure: not determined
 (at 20 °C)
 Density: 0,93 g/cm³
 Relative vapour density: not determined

9.2. Other information**Information with regard to physical hazard classes**

Sustaining combustion: No data available

Other safety characteristics

Solvent separation test: not determined
 Solvent content: not determined

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 8 of 17

Solid content: not determined

Evaporation rate: not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from heat. Danger of explosion!

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 9 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
541-02-6	Decamethylcyclopentasiloxane				
	oral	LD50 > 5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 > 2000 mg/kg	Rabbit	ECHA Dossier	
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 > 2000 mg/kg	Rabbit.	ECHA Dossier	
	inhalation (4 h) vapour	LC50 > 5,3 mg/l	Rat	ECHA Dossier	
108-88-3	toluene				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 (28,1) mg/l	Rat	ECHA Dossier	
67-56-1	methanol				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	ATE 0,5 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 10 of 17

Based on available data, the classification criteria are not met.

toluene:

In-vitro mutagenicity: Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test); Result: negative. Literature information: ECHA Dossier; Carcinogenicity: Method: [inhalative, OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)]; Species: Rat ; Exposure duration: 2 years ; Result: NOAEC = 4522 mg/m³; Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study); Species: Rat ; Result: NOAEC = 1875 mg/m³; Literature information: ECHA Dossier ; Developmental toxicity/teratogenicity: Method: [inhalative, EPA OTS 798.4350 (Inhalation Developmental Toxicity Screen)]; Species: Rabbit; Exposure duration: 20d ; Result: NOEC = 2812 mg/kg; Literature information: ECHA Dossier

methanol:

Germ cell mutagenicity: Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test). Species: Mouse.; Result: negative. Literature information: ECHA Dossier; Carcinogenicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies). Length of test: 18 m. Species: Mouse.; Result: NOAEC = 1,3 mg/l; Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study). Species: Rat. Result: NOAEC = 1,3 mg/l; Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study). Species: Rabbit. Result: NOAEL = 1000 mg/kg.

Distillates (petroleum), hydro-treated light; Kerosine - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells) , OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test), OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative. Literature information: ECHA Dossier

In vivo mutagenicity/genotoxicity:

Method: OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test), OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test); Result: negative.;nLiterature information: ECHA Dossier

Reproductive toxicity:
Method:-; Species: Sprague-Dawley Rat; Exposure route : oral; Result: NOAEL > 1500 mg/kg; Literature information: ECHA Dossier

Developmental toxicity/teratogenicity:

Method:OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Sprague-Dawley Rat ; Exposure route: oral; Result: NOAEL = 1000 mg/kg; Literature information: ECHA Dossier

Xylene:

In-vitro mutagenicity: Method: EU Method B.10 (Mutagenicity - In Vitro Mammalian Chromosome Aberration Test); Result: negative. Literature information: ECHA Dossier; Developmental toxicity/teratogenicity : NOAEL >= 500ppm (OECD Guideline 414); Literature information: ECHA Dossier; Carcinogenicity: Method: EU Method B.32 (Carcinogenicity Test); Species: Rat.; Exposure duration: 24 months. Result: NOAEL = 500 mg/kg; Literature information: ECHA Dossier; Reproductive toxicity: Method: (inhalation.): EPA OPPTS 870.3800 (Reproduction and Fertility Effects); Species: Rat ; Exposure duration: 14d.Results: NOAEC = 500 ppm. Literature information: ECHA Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 11 of 17

May cause damage to organs through prolonged or repeated exposure. (stoddard solvent; Low boiling point naphtha - unspecified)

toluene:

Subchronic oral toxicity: Method: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents); Species: Mouse. ; Exposure duration: 90d; Result: NOEL = 625 mg/kg ; Literature information: ECHA Dossier; Subchronic inhalation toxicity: Method: -; Species: Rat. Exposure duration: 1 year ; Result: NOAEC = 1131 mg/m³; Literature information: ECHA Dossier

methanol:

Chronic inhalative toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies). Length of test: 12 m . Exposure time: 20 h/d. Species: Rat. Result: Result: NOAEC = 1,3 mg/l. Literature information: ECHA Dossier

Distillates (petroleum), hydro-treated light; Kerosine - unspecified:

Subchronic oral toxicity: Method:-; Species: Sprague-Dawley Rat ;Exposure duration: 90d; Result: NOAEL = 750 mg/kg ; Literature information: ECHA Dossier; Subchronic inhalation toxicity: Method:OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day); Species: Mouse; Exposure duration: 90d; Result: NOAEC = 1000 mg/kg; Literature information: ECHA Dossier; Subchronic oral toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Species: Sprague-Dawley Rat ; Exposure duration: 28d; Result: NOAEC = 0,5 ml/kg; Literature information: ECHA Dossier

Xylene:

Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat ; Exposure duration: 90d. Result: NOAEL = 750 mg/kg (male.) = 150 mg/kg (female.); Literature information: ECHA Dossier

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards**Endocrine disrupting properties**

No data available.

Further information

Solvent

Symptoms: Depression of the central nervous system. Liver and kidney damage. drowsiness. vomiting.

Nausea. Dizziness. unconsciousness. Impaired consciousness. Intoxication. erythema (redness)

SECTION 12: Ecological information**12.1. Toxicity**

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 12 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
541-02-6	Decamethylcyclopentasiloxane					
	Acute fish toxicity	LC50 mg/l	[> 0,019]	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	[> 0,0129]	96 h	Pseudokirchneriella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	[> 0,0029]	48 h	Daphnia magna	ECHA Dossier
	Fish toxicity	NOEC mg/l	[0,0149]	90 d	Oncorhynchus mykiss (Rainbow trout)	ECHA Dossier
	Algae toxicity	NOEC mg/l	[> 0,0129]	4 d	Pseudokirchneriella subcapitata	ECHA Dossier
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified					
	Acute algae toxicity	ErC50 mg/l	EL50: 1-3	72 h	Pseudokirchneriella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EL50	1,4 mg/l	48 h	Daphnia magna	ECHA Dossier
108-88-3	toluene					
	Acute fish toxicity	LC50 mg/l	(5,5)	96 h	Oncorhynchus kisutch	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	(12,5)	72 h		GESTIS
	Acute crustacea toxicity	EC50 mg/l	(3,78)	48 h	Ceriodaphnia dubia	ECHA Dossier
	Acute bacteria toxicity	(134 mg/l)		3 h	Chlorella vulgaris and Chlamydomonas angulosa	ECHA Dossier
67-56-1	methanol					
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)

12.2. Persistence and degradability

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
541-02-6	Decamethylcyclopentasiloxane				
	OECD Guideline 310	0,14%	28	ECHA Dossier	
	Not easily bio-degradable (according to OECD-criteria).				
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified				
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	61	28	ECHA Dossier	
67-56-1	methanol				
	other guideline	76%	20	ECHA Dossier	
	Easily biodegradable (concerning to the criteria of the OECD)				

12.3. Bioaccumulative potential

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 13 of 17

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
541-02-6	Decamethylcyclopentasiloxane	8,023
108-88-3	toluene	2,73
546-68-9	Titanium tetraisopropanolate	0,05
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
541-02-6	Decamethylcyclopentasiloxane	7060	Pimephales promelas	ECHA Dossier
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point naphtha - unspecified, toluene)

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 14 of 17

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L

Excepted quantity: E2

Transport category: 2

Hazard No: 33

Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point naphtha - unspecified, toluene)

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L

Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point naphtha - unspecified, toluene)

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Marine pollutant: NO

Special Provisions: 274

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point naphtha - unspecified, toluene)

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 15 of 17

Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
 Decamethylcyclopentasiloxane

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 48, Entry 69, Entry 70

2010/75/EU (VOC): not determined

2004/42/EC (VOC): not determined

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Safety Data Sheet according to UK-REACH Regulation

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

UK REACH Appendix XVII, No (mixture): 3, 40, 48, 69, 70

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1.0; 24.08.2021, Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 16 of 17

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 CanCoat EVO

Revision date: 24.08.2021

Product code: G0033

Page 17 of 17

H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)