according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

GYEON Q2 Matte EVO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Vehicle protective product - ceramic coating designed for paintwork Enthusiasts and professional use (End consumer)

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Gyeon Technology

Street: 1405-538, 212, Gasan digital 1-ro Place: Geumcheon-gu, Seoul, Korea

Telephone: +82-10-4339-3599 Contact person: Robert Gyeon

e-mail: sales@gyeonquartz.com

Responsible Department: Dr. Gans-Eichler e-mail: info@tge-consult.de

Chemieberatung GmbH Tel.: +49(0)2534 6441185 Otto-Hahn-Str. 36 www.tge-consult.de

D-48161 Münster

Supplier

Company name: Gyeon UK Ltd

Street: 20 Crichiebank Business Centre, Mill Road

Place: GB-AB51 5NQ Inverurie e-mail: hello@gyeonquartz.uk

Contact person: Richard Cooper Telephone: +44 (0)7984 056790

1.4. Emergency telephone +82-10-4339-3599

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Flammable liquid: Flam. Liq. 2 Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 2 of 16

Hazard components for labelling

Distillates (petroleum), hydro- treated light; Kerosine - unspecified Naphtha (petroleum), light alkylate; Low boiling point modified naphtha stoddard solvent; Low boiling point naphtha - unspecified toluene

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 3 of 16

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification	•	<u>'</u>	
64742-47-8	Distillates (petroleum), hydro- trea	ated light; Kerosine - unspecified		40 - < 45 %
	265-149-8			
	Asp. Tox. 1; H304	•	<u> </u>	
64741-66-8	Naphtha (petroleum), light alkylat	e; Low boiling point modified na	ohtha	10 - < 12 %
	265-068-8	649-276-00-X		
	Asp. Tox. 1; H304	•		
8052-41-3	stoddard solvent; Low boiling poil	nt naphtha - unspecified		3 - < 5 %
	232-489-3	649-345-00-4		
	Flam. Liq. 3, STOT RE 1, Asp. To	ox. 1, Aquatic Chronic 2; H226 H	372 H304 H411	
108-88-3	toluene	1 - < 3 %		
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, H373 H304			
107-46-0	Hexamethyldisiloxane	1 - < 3 %		
	203-492-7			
	Flam. Liq. 2, Aquatic Acute 1, Aq			
546-68-9	Titanium tetraisopropanolate	1 - < 3 %		
	208-909-6			
	Flam. Liq. 3, Eye Irrit. 2, STOT SI			
67-56-1	methanol			0.3 - < 0.5 %
	200-659-6	603-001-00-X		
	Flam. Liq. 2, Acute Tox. 3, Acute			
1112-39-6	dimethoxydimethylsilane			0.1 - < 0.2 %
	214-189-4			
	Flam. Liq. 2, Repr. 2; H225 H361			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

Specific Con	c. Limits, Wi-tac	tors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
64742-47-8	265-149-8	Distillates (petroleum), hydro- treated light; Kerosine - unspecified	40 - < 45 %
	inhalation: LC5 mg/kg	0 = (> 5,3) mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000	
108-88-3	203-625-9	toluene	1 - < 3 %
	inhalation: LC5 mg/kg	0 = (28,1) mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000	
67-56-1	200-659-6	methanol	0.3 - < 0.5 %
	I	= 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = : ATE = 100 mg/kg	

Further Information

- Naphtha (petroleum), light alkylate; Low boiling point modified naphtha (P)
- stoddard solvent; Low boiling point naphtha unspecified (P)

Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 4 of 16

substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7).

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 5 of 16

For non-emergency personnel

Remove persons to safety. Remove all sources of ignition. Ventilate affected area.

Wear personal protection equipment. (See section 8.)

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

$\underline{\textbf{7.2. Conditions for safe storage, including any incompatibilities}}$

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 6 of 16

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

8.2. Exposure controls











Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Skin protection

Wear fire/flame resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 7 of 16

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3 The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid.
Colour: transparent
Odour: characteristic

Test method

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

110 °C

boiling range:

Flash point: 13 °C ISO 3679

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:not determinedUpper explosion limits:not determinedAuto-ignition temperature:not determinedDecomposition temperature:not determined

Oxidizing properties

none.

pH-Value: not determined Viscosity / dynamic: not determined

(at 40 °C)

Viscosity / kinematic: not determined

(at 20 °C)

Flow time: not determined Water solubility: not miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: SECTION 12: Ecological information Vapour pressure: not determined

(at 20 °C)

Density: 0,85-0,9 g/cm³
Relative vapour density: not determined

9.2. Other information

Other safety characteristics

Solvent separation test:

Solvent content:

not determined
not determined
not determined
rate:

not determined
not determined

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 8 of 16

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from heat. Danger of explosion!

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 9 of 16

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-47-8	Distillates (petroleum), hydro- treated light; Kerosine - unspecified							
	oral	LD50 mg/kg	> 5000	Rat	ECHA Dossier			
	dermal	LD50 mg/kg	> 2000	Rabbit.	ECHA Dossier			
	inhalation (4 h) vapour	LC50 mg/l	(> 5,3)	Rat	ECHA Dossier			
108-88-3	toluene							
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier			
	dermal	LD50 mg/kg	>5000	Rabbit	ECHA Dossier			
	inhalation (4 h) vapour	LC50 mg/l	(28,1)	Rat	ECHA Dossier			
67-56-1	methanol							
	oral	ATE mg/kg	100					
	dermal	ATE mg/kg	300					
	inhalation vapour	ATE	3 mg/l					
	inhalation aerosol	ATE	0,5 mg/l					

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 10 of 16

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydro-treated light; Kerosine - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells), OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test), OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative. Literature information: ECHA Dossier In vivo mutagenicity/genotoxicity:

Method: OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test), OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test); Result: negative.;nLiterature information: ECHA Dossier Reproductive toxicity:

Method:-; Species: Sprague-Dawley Rat; Exposure route: oral; Result: NOAEL > 1500 mg/kg; Literature

information: ECHA Dossier

Developmental toxicity/teratogenicity:

Method:OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Sprague-Dawley Rat;

Exposure route: oral; Result: NOAEL = 1000 mg/kg; Literature information: ECHA Dossier

toluene:

In-vitro mutagenicity: Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test); Result: negative. Literature information: ECHA Dossier; Carcinogenicity: Method: [inhalative, OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)]; Species: Rat; Exposure duration: 2 years; Result: NOAEC = 4522 mg/m3; Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study); Species: Rat; Result: NOAEC = 1875 mg/m3; Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: [inhalative, EPA OTS 798.4350 (Inhalation Developmental Toxicity Screen)]; Species: Rabbit; Exposure duration: 20d; Result: NOEC = 2812 mg/kg; Literature information: ECHA Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (stoddard solvent; Low boiling point naphtha - unspecified)

Distillates (petroleum), hydro-treated light; Kerosine - unspecified:

Subchronic oral toxicity: Method:-; Species: Sprague-Dawley Rat ;Exposure duration: 90d; Result: NOAEL = 750 mg/kg; Literature information: ECHA Dossier; Subchronic inhalation toxicity: Method:OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day); Species: Mouse; Exposure duration: 90d; Result: NOAEC = 1000 mg/kg; Literature information: ECHA Dossier; Subchronic oral toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Species: Sprague-Dawley Rat; Exposure duration: 28d; Result: NOAEC = 0.5 ml/kg; Literature information: ECHA Dossier

toluene

Subchronic oral toxicity: Method: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents); Species: Mouse.; Exposure duration: 90d; Result: NOEL = 625 mg/kg; Literature information: ECHA Dossier; Subchronic inhalation toxicity: Method: -; Species: Rat. Exposure duration: 1 year; Result: NOAEC = 1131 mg/m3; Literature information: ECHA Dossier

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

No data available.

SECTION 12: Ecological information

12.1. Toxicity

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 11 of 16

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
64742-47-8	Distillates (petroleum), hy	Distillates (petroleum), hydro- treated light; Kerosine - unspecified							
	Acute algae toxicity	ErC50 3 mg/l	EL50: 1-	72 h	Pseudokirchneriella subcapitata	ECHA Dossier			
	Acute crustacea toxicity	EC50 1,4 mg/l	EL50:	48 h	Daphnia magna	ECHA Dossier			
108-88-3	toluene								
	Acute fish toxicity	LC50 mg/l	(5,5)	96 h	Oncorhynchus kisutch	ECHA Dossier			
	Acute algae toxicity	ErC50 mg/l	(12,5)	72 h		GESTIS			
	Acute crustacea toxicity	EC50 mg/l	(3,78)	48 h	Ceriodaphnia dubia	ECHA Dossier			
	Acute bacteria toxicity	(134 mg/l)		3 h	Chlorella vulgaris and Chlamydomonas angulosa	ECHA Dossier			
67-56-1	methanol								
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	ECHA Dossier			
	Acute algae toxicity	ErC50 mg/l	22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	DIN 38412 Teil 11		

12.2. Persistence and degradability

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation						
64742-47-8	Distillates (petroleum), hydro- treated light; Kerosine - unspecified						
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	61	28	ECHA Dossier			
67-56-1	methanol						
	other guideline	76%	20	ECHA Dossier			
_	Easily biodegradable (concerning to the criteria of the OECD)						

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
546-68-9	Titanium tetraisopropanolate	0,05
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 12 of 16

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point

naphtha - unspecified, toluene)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 13 of 16

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point

naphtha - unspecified, toluene)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point

naphtha - unspecified, toluene)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

Excepted quantity:

Excepted F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Low boiling point

naphtha - unspecified, toluene)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 14 of 16

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 48, Entry 69

2010/75/EU (VOC): not determined 2004/42/EC (VOC): not determined

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

Safety Data Sheet according to UK-REACH Regulation

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

UK REACH Appendix XVII, No (mixture): 3, 40, 48, 69

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1.0; 31.08.2016, Initial release

Rev. 2.0; 08.03.2019, Changes in chapter: 1 - 16

Rev. 3.0; 11.05.2020, Revision, Changes in chapter: 1 - 16

Rev. 3.1; 02.02.2021, Revision

Rev. 4.0; 20.05.2021, Revision (Changes in chapter: 1-16)

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European LIst of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 15 of 16

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method. Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

according to UK REACH Regulation

GYEON Q2 Matte EVO

Revision date: 30.08.2021 Product code: G0036 Page 16 of 16

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)