



## PSDH121 1or2H/1C DIGITAL NON-PROGRAMMABLE HEAT PUMP THERMOSTAT

- Electronic Accuracy
- Can Be Mounted Horizontally or Vertically (Patent Pending)
- Large, Easy-To-Read Digital Display
- EL (Electro Luminescent) Backlight
- Temperature Swing Adjustment to as close as + or - ¼° F/C
- System or Battery Powered
- Low Battery Indicator
- Auxiliary and Emergency Heat Indicator
- Emergency Heat Position
- Optional Decorative Wall Plate
- 5 or 2 Minute Compressor Delay
- 5 or 2 Minute Minimum "on" Time
- Fahrenheit or Celsius
- "O" and "B" Terminals


### **COMPATIBLE WITH:**


 1 or 2 Stage Heat / 1 Stage Cool Heat Pumps

### **NOT COMPATIBLE WITH:**

- 3 Wire Hydronic Systems
- Multi-Stage Gas or Oil Furnaces
- Line Voltage Systems (Without Transformer)

# LUX**PRO**® PSDH 121





### **GENERAL DESCRIPTION:**

45/4" (118mm) wide x 31/4" (82mm) tall x 7/4" (22.5mm) deep

Optional Wall Plate: Decorative wall plate is available for thermostat.

**Description:** Battery Powered digital thermostat with a large easy-to-read display with backlight. Temperature control adjustable from factory set at + or - ½° F/C.

### **SPECIFICATIONS:** •

**Electrical Ratings:** 1½ AMPS at 24v AC. System or Battery Powered: 2 "AA" Batteries (included).

**Temperature Control Range**:  $45^{\circ}$ F to  $90^{\circ}$ F ( $7^{\circ}$  to  $32^{\circ}$ ). Accuracy:  $\pm 1^{\circ}$ F over a range of  $50^{\circ}$ F to  $95^{\circ}$ F.

**Compatibilities:** 1 or 2 Stage Heat / 1 Stage Cool Heat Pumps. 2 Wire Hydronic Systems and Hydronic Air Handling Systems. Solid Pin Connectors Allow Usage with both 24V and Millivolt Equipment.

#### **Environmental Limits:**

Moisture and Dust: meets IP20.

Operating Humidity: 20% to 90% non-condensing.

Operating Temperature: +32°F to +95°F (+0°C to +35°C). Storage Temperature: -4°F to +130°F (-20°C to +54°C). Electrical Immunity: meets relevant CE specifications.



**LUX Products Corporation** 6000 | Commerce Parkway • Mt. Laurel, NJ 08054 (856) 234-7905 • FAX (856) 234-7825 • www.luxproproducts.com

JOB NAME:			DATE:
CONTRACTOR:			UNIT DESIGNATION:
ENGINEER:			MODEL NO.:
SUBMITTED FOR:	APPROVAL	RECORD	LOCATION: