



netool.io Lite

With the netool.io you combine all important tools for network analysis and troubleshooting in one device. Thanks to its compact design, the netool.io fits anywhere. Operations and evaluations take place independently of the operating system using the free APP for iOS or Android. This allows for flexibility in the analyzing of the network, through switch ports.

Supported System iOS, iPadOS, Android

Mechanical

Dimensions 107.95 x 44.45 x 19.05mm (4.25"x1.75"x0.75")
Weight 86g (3oz)

Battery

Type Polymer Lithium-ion Cell
Size 2500mAh 9.25Wh
Voltage 3.7V
Run time 12 hours

Charging

USB-C (Charing) 1.0Amps
UCB-C (Data) Future use
Ether RJ45

Phone/Tablet Communication

BLE 5.0 iOS, iPadOS, Android
WiFi 2.4ghz iOS, iPadOS, Android

Protocols Detected

Discovery protocols LLDP, CDP, EAP, CDPv2, EDP, FDP, SONMP
Tagged VLAN Ids 802.1Q
DHCP IPv4, IPv6
STP Spanning tree via packet sniffing.
LACP Link Aggregation Control Protocol

Connectivity Tests

ICMP (Ping) From main app menu.
HTTP/HTTPs To any custom URL
Trace Route To any custom address
802.1X Port authentication
Certifications FCC, CE, RoHS, C-Tick, A-Tick
Public IP Detect external IP address of the network

Netool.io Cloud Sync discovered data with netool.cloud
Sharing Share discovered data via multiple platforms.