



U-TAP SDI

The U-TAP 3G-SDI USB 3.0 capture devices brings professional connectivity and high quality video capture to your laptop or workstation. U-TAP SDI is bus powered with the ability to simply and easily bring in video across 3G-SDI for use within a wide range of software without any drivers to install, as it's supported directly in macOS X®, Windows® and Linux®.

\$345 US MSRP

<https://www.aja.com/products/u-tap-sdi>

Video Formats

- Video (SDI)
 - (HD) 1920 x 1080p 50, 59.94, 60 (Level A or B-DL)
 - (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30
 - (HD) 1920 x 1080i 50, 59.94, 60
 - (HD) 1280 x 720p 50, 59.94, 60
 - (SD) 625i 50
 - (SD) 525i 59.94
 - YCbCr, 4:2:2, 10-bit
- Scaled (USB), Frame rates for all formats: 7.5, 15, 25, 29.97, 30, 50, 59.94, 60
 - 1920 x 1080p
 - 1440 x 1080p
 - 1280 x 720p
 - 1024 x 576p
 - 960 x 540p
 - 856 x 480p
 - 800 x 600p
 - 768 x 576p
 - 720 x 576p
 - 720 x 480p
 - 640 x 480p
 - 640 x 360p
 - 432 x 240p
 - 352 x 288p
 - 320 x 240p
 - 176 x 144p

Notes:

1. PsF formats are not supported.
2. Host system specifications/performance will govern what video formats are possible.

Video Input Digital

- 3G-SDI, SMPTE-259/292/424, YCbCr 4:2:2 (1x BNC)

Video Loop Output

- 1x 3G-SDI (1x BNC)

Audio Input Digital

- 2-channel, 24-bit SDI embedded audio, 48 kHz sample rate

Capture Video

- 16-bits/pixel, YUV (input video will be truncated as required)

Capture Audio

- 2-channel, 16-bit, 48 kHz sample rate (input audio will be truncated as required)

Host Interface

- USB 3.0/USB 2.0 UVC/UAC compliant

Size (w x d x h)

- 4.1" x 2.4" x 1.0" (104.14 x 60.96 x 25.4 mm)

Weight

- 0.3 lb (0.2 kg)

Power



- 5V USB bus powered; 4W max

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)