

CONCRETE SOLVENT PRIMER

RESOURCE CODE 210009

MAY 2019

PAGE 1 OF 3



Description & Uses

Baxta Concrete Solvent Primer is a solvent-based acrylic primer designed to eliminate uneven substrate absorption on dense or difficult substrates, ensuring optimum adhesion of texture coating systems.

Features & Benefits

- | | |
|--|---|
| <ul style="list-style-type: none"> Stabilises irregularities in substrate absorption Interior and exterior use | <ul style="list-style-type: none"> Ensures strong adhesion of topcoats to the substrate Fast drying |
|--|---|

Colours

Transparent with a white tinge to act as an application marker. Do not tint.

Properties & Performance Guide

Dry & Recoat Times	<p>Surface Dry - 30 minutes Recoat - 2 hours Fully Cured - 7 days</p> <p>Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.</p>
Coverage per Coat	Up to 14 M ² /L depending on the surface texture, porosity and method of application.
Thinning	Not required.
Clean Up	<p>Clean up with L780 Industrial Universal Thinner away from drains. Soak all used cloths in water after use as they may self-ignite.</p> <p>Protect Our Environment: Do not pour leftover paint down the drain. To dispose of unwanted paint see paintback.com.au.</p> <p>Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle containers via recycling programs. Check with your local council first.</p>

CONCRETE SOLVENT PRIMER

RESOURCE CODE 210009

MAY 2019

PAGE 2 OF 3

Recommended Substrate Conditions & Preparation

Work Area: Care should be taken to keep product off windows and adjacent surfaces that are not to be coated, as product can be very difficult to remove once allowed to dry. Use drop sheets to cover surroundings surfaces. Ensure air movement and ventilation while painting. Keep doors and windows open.

Substrate Condition: Baxta Concrete Solvent Primer is specifically designed for pre-cast, tilt-up and glass reinforced concrete. Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, application must be carried out according to Baxta's recommendation.

Surface Prep: Ensure the surface is clean and dry. All substrates must be free of dirt, grease, oil, mould, release agents, bondbreakers or any other contaminants that may interfere with adhesion. Fresh cementitious substrates should be left for a minimum 28 days before coating. There must be less than 15% moisture content in the surface at the time of coating to ensure optimum coating performance. All substrates must be installed as per manufacturers' specifications prior to application.

Application Guide

Stir well before and during use with a broad paddle reaching to the bottom of the can and using an upward lifting action.

Apply one full, even coat by brush, roller or airless spray.

Airless spray settings: Tip 519-521, Pressure 1500-2000psi.

Application should not be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process. Drying time may be longer in cold or humid conditions. Do not apply when rain or dew is likely. Keep sheltered from frosts and rain for a minimum 48 hrs after completion dependent on climatic conditions.

Additional Data

Available in 15L.

Baxta Concrete Solvent Primer must be topcoated within two weeks of application.

Avoid exposure to steam and condensation for 48 hours after application of final coat.

Leave 7 days after application of final coat before washing. Wash using a sponge or soft cloth with warm water and mild detergent. Avoid harsh scrubbing and strong household cleaners.

Not suitable for walk-on surfaces.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Store in a secure, cool and well ventilated place. Keep container tightly closed.

Do not use for any other purpose other than as specified.

Manufacturers Comment

This product has been designed as part of a totally integrated coating system. Failing to follow application instructions or use with other manufacturer's product, could result in detrimental effects on product performance for which Baxta Industries Pty Ltd cannot be held responsible.

CONCRETE SOLVENT PRIMER

RESOURCE CODE 210009

MAY 2019

PAGE 3 OF 3

Safety Data	
First Aid Instructions	<p>For advice, contact the Poisons Information Centre on 131 126 (Australia) or a doctor.</p> <p>If in eyes, wash out immediately with water. Remove contact lenses if present and easy to do so, continue rinsing.</p> <p>If skin contact occurs remove contaminated clothing and flush contaminated skin with water.</p> <p>If inhaled remove from contaminated area to fresh air.</p> <p>If swallowed, do not induce vomiting. Give a glass of water to drink.</p>
Safety Directions	<p>FLAMMABLE.</p> <p>HAZARDOUS: Contains 30-60% liquid hydrocarbons.</p> <p>Keep away from sources of ignition.</p> <p>No smoking.</p> <p>Keep closed when not in use.</p> <p>Keep out of reach of children.</p> <p>Avoid contact with skin and eyes.</p> <p>Ensure adequate ventilation during use.</p> <p>Avoid prolonged breathing of vapour.</p> <p>Wash hands thoroughly after use.</p>
Further Information	<p>Safety Data Sheet and Product Information can be found at www.baxta.com.au or by calling 1300 85 55 40.</p>