

XERO PREP & CEILING WHITE

RESOURCE CODE 210016
FEBRUARY 2020
PAGE 1 OF 3



Description & Uses

Baxta Xero Prep & Ceiling White is a premium quality, water-based sealer-undercoat and ceiling flat coating. Developed for spray and backroll application to achieve high work efficiency in commercial and residential environments and provides an ultra flat high coverage ceiling finish.

Features & Benefits

- | | |
|--|--|
| <ul style="list-style-type: none"> • Dual purpose • Easy, fast application | <ul style="list-style-type: none"> • Time saving • Low VOC |
|--|--|

Colours & Gloss

White – Can be tinted to White Base colours. Due to the high opacity of this product, tinted colours will appear lighter than the standard colour.

Flat (Gloss level <2 at 60 degrees).

XERO PREP & CEILING WHITE

RESOURCE CODE 210016
FEBRUARY 2020
PAGE 2 OF 3

Properties & Performance Guide	
Dry & Recoat Times	Surface Dry - 30 minutes Recoat - 2 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 10 M ² /L depending on the surface texture, porosity and method of application.
Thinning	Thinning is generally not required. If necessary to aid spray atomisation, thin with up to 50ml of water per litre of paint.
Clean Up	Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. To dispose of unwanted paint see paintback.com.au . Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle containers via recycling programs. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 16g/Litre.

Recommended Substrate Conditions & Preparation

Work area: Care should be taken to keep product off windows and adjacent surfaces that are not to be coated, as product can be very difficult to remove once allowed to dry. Use drop sheets to cover surroundings surfaces. Ensure air movement and ventilation while painting. Keep doors and windows open.

Substrate Condition: Recommended surfaces included paper-faced plasterboard, masonry, internal ceilings and pre-painted surfaces. Baxta Xero Ceiling White must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants.

Surface Prep: Surfaces should be clean, dry and free from loose or crumbling material, oil and release agents. Repair any damaged areas, fill cracks, nail holes and imperfections. Previously painted surfaces should be sanded to a dull finish.

Application Guide

Stir well before and during use with a broad paddle reaching to the bottom of the can and using an upward lifting action.

Apply one full, even coat as a sealer-undercoat by airless spray to all suitably prepared surfaces. Backroll to provide an optimal finish. On ceilings apply further finish coats by airless spray and backrolling.

Suggested spray settings: 517 spray tip and 2000-23000psi.

For walls and areas other than ceilings apply appropriate Baxta coatings as the finish coats by brush, roller, or spray. Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.

XERO PREP & CEILING WHITE

RESOURCE CODE 210016

FEBRUARY 2020

PAGE 3 OF 3

Additional Data

Available in 15L.

Check colour is correct before applying. Manufacturer and distributor will accept no liability once product has been applied.

For large projects box (or mix) pails to ensure colour consistency.

For ceilings in wet areas or where a washable ceiling finish is required, use Baxta Xero Plus Interior Paint.

Avoid exposure to steam and condensation for 48 hours after application of final coat.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Store in a secure, cool and well ventilated place. Keep container tightly closed.

Do not use for any other purpose other than as specified.

Manufacturers Comment

This product has been designed as part of a totally integrated coating system. Failing to follow application instructions or use with other manufacturer's product, could result in detrimental effects on product performance for which Baxta Industries Pty Ltd cannot be held responsible.

Safety Data

<p>First Aid Instructions</p>	<p>For advice, contact the Poisons Information Centre on 131 126 (Australia) or a doctor. If in eyes, wash out immediately with water. Remove contact lenses if present and easy to do so, continue rinsing. If skin contact occurs remove contaminated clothing and flush contaminated skin with water. If inhaled remove from contaminated area to fresh air. If swallowed, do not induce vomiting. Give a glass of water to drink.</p>
<p>Safety Directions</p>	<p>Keep out of reach of children. Avoid contact with skin and eyes. Ensure adequate ventilation during use. Avoid prolonged breathing of vapour. Wash hands thoroughly after use.</p>
<p>Further Information</p>	<p>Safety Data Sheet and Product Information can be found at www.baxta.com.au or by calling 1300 85 55 40.</p>