Combo HD Video System II

HD video system with integrated light source and still/video image capturing



The Combo HD Video System II incorporates our best HD single chip camera head with high intensity LED and integrated still image and video capturing capabilities. This system is simple to control and produces excellent, high-definition images. The platform has white balance, light intensity adjustments, and a built-in, user-friendly menu so you can customize the system to your individual needs. In addition to the built-in light source, the Combo HD II also includes integrated still image and video capturing which can easily be transferred on a USB hard drive. Image and video capturing is easily done by depressing a button on the camera head, pushing a button on the control unit, or depressing a footswitch (not included). All images and video are captured in High-Definition and can be easily put into a patient's electronic medical records.

This system also includes a state-of-the-art anti-moire feature that will help to drastically reduce the "honeycomb" effect commonly seen on fiberoptic nasopharyngoscopes. By simply depressing the "Flex" button on the front of the unit, you can drastically improve the image quality and detail of any image with a fiberoptic scope.

The Combo HD Video System II includes a 28mm focusable video coupler that allows the attachment of any scope with a standard eyepiece.

- HD camera with integrated LED light source
- "Flex" feature reduces fiberscope honeycomb effect
- Automatic light control with manual override

- Built-in still image and video capturing
- Simple to operate
- 28mm focusable coupler



Combo HD Video System II HD video system with integrated light source and still/video image capturing

Technical Data

Camera head:

Voltage range (current consumption): Frequency: Device protection:

Video system:

Recording:

Lamp:

Light guide connection:

Connections:

Projection class (acc. to IEC 60601-1): Safety class: IP code: Standard:

Features:

Dimensions:

Delivery contains:

Optional Accessories

Footswitch

Camera head with push buttons



Weight: approx. .5 lbs Size: d = 1.5"; l = 3" (without cable bend relief)



- Image sensor: 1/2" CMOS
- 100 240 V (95 VA)
- 50 60 Hz (interlaced scan)
- 2x T3, 15 A
- Image resolution: full HD 1920 x 1080
- Image format: JPG 1920 x 1080
- Video format: Full HD 1920 x 1080
- Connection: USB
- LED lamp
- Storz

Video out terminal

- 1x HDMI
- 1x DVI
- 1x SDI
- 1x VIDEO
- |
- BF
- 20
- IEC 60601-1-2
- White balance
- Digital zoom
- On-screen-menu
- Flex button
- Control unit 11.5" x 5" x 11"; Weight 6 lbs.
- CCU, camera head with 10 ft. cable, power cable, HDMI - DVI cable, HDMI cable, user manual

- TV resolution > 900 lines
- White balance automatically, with data hold Sensitivity: < 3 lux (1/1.4)

Other connections

- 1x USB (Service)
- 1x Remote IN (footswitch)
- 1x RJ45 (Service)

- Freeze function
- 8 endoscope presets
- Integrated menu

5415 JEDMED Court • St. Louis, MO 63129-2221 • Phone (314) 845-3770 • Fax (314) 845-3771 • Email: info@jedmed.com • Website: www.jedmed.com