Tech Spec Sheet: QUANTAR SCOM-7330 with Logic

Cable Type 1	24 AWG 7/32 Stranded 10 Conductor Mylar Shielded Cable with drain
Cable Type 2, 3	22 AWG 7/32 Stranded 3 Conductor Cable
Cable Insulation 1, 2, 3	Polyvinyl Chloride
Assembled Length (from end to end connection)	68"
Connector 1	50-pin SCSI right angle connector
Connector 2	9-pin D-SUB zinc plated metal housing
Connector 3	Phoenix Contact COMBINCON MSBT 2-pin terminal block
Connector 4	25-pin D-SUB Male Acrylonitrile Butadiene Stryene
Connector 4	23-piii D-30B Male Acrylollittile Butaulelle Stryelle
Contact Finish Connector 1	Phosphor- Bronze
	· · · · · · · · · · · · · · · · · · ·
Contact Finish Connector 2	Phosphor- Bronze
Contact Finish Connector 3	Tin
Contact Finish Connector 4	Phosphor- Bronze
Minimum Bend Radius	1.5"
Material Finish	Synthetic black braided sleeving
Product Weight (oz)	18
Mariana d	
Warranty	1 year from date of manufacture parts, labor and manufacturing defects
Indoor/Outdoor	Indoor
Indoor/Outdoor	Indoor