oirex=

AXR.UCGN.3G

Refrigerated Undercounter 3 Glass Doors - 1/1GN

Product Information:

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (0°C 6°C) •
- Fan forced ducted cooling for uniformed performance throughout the entire refrigerator
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility .
- Stainless Steel worktop as standard
- 1/1GN shelf configuration with adjustable runners .
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative • internal design
- High quality components including highly efficient compressors and EC fans
- Double glazed heated glass door for exceptional display and minimal condensation
- Self-closing doors with lock fitted as standard
- Supplied on standard and lockable castors for a 840mm finish height. Optional spacer to increase to 900mm working height
- 2 and 4 door models also available, with glass or solid doors

Designed and Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty


Optional Accessories:


- Height increase channel spacer pair (AXR.UCGN.CH) (2 required) •
- 1/1GN shelf with runners (AXR.UCGN.SHELFKIT) •

Specifications

Model	AXR.UCGN.3G
W x D x H (mm)	1795 x 700 x 840
Weight	133kg
Packed Dimensions (mm)	1825 x 730 x 88
Packed Weight	157kg
Net Capacity	276 Litres
Operation	0°C - 6°C
Refrigerant	R290
Climate Class	4
Max Ambient	38°C
Power	0.33kW 230VAC 10A plug & lead

UCGN.3G 700 x 840 730 x 880 res °C







SIDE VIEW



Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: 02 - 23/07/2021 - A www.stoddart.com.au www.stoddart.co.nz

