



## Gasmax 6 Burner With Oven Flame Failure GBS6TS

### Quick Overview

- Heavy-Duty Burners With Flame Failure
- Stainless steel construction
- Natural gas
- Cast iron open burners
- Thermostat (100°&#x84;&#x83;- 300°&#x84;&#x83; ) controlled oven
- Welded frame structure for best stability
- Flame failure control valve
- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Fully Insulated Stainless steel oven door
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing
- 3/4°&#x80;&#x9D; rear gas connection
- Continuous pilot
- Each burner power is 38MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400°&#x84;&#x83; heat

### Description

Gasmax 6 Burner With Oven Flame Failure GBS6TS

### Key Features

- Heavy-duty burners With Flame Failure
- Stainless steel construction
- Natural gas
- Cast iron open burners
- Thermostat (100 - 300 ) controlled oven
- Welded frame structure for best stability
- Flame failure control valve

- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Fully Insulated Stainless steel oven door
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing
- 3/4 " rear gas connection
- Continuous pilot
- Each burner power is 38MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400 ° heat

2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice

Your Shipping Specifications

Net Weight (Kg)	167
Width (mm)	914
Depth (mm)	855
Height (mm)	1128
Packing Width (mm)	1030
Packing Depth (mm)	1040
Packing Height (mm)	890
Power	258MJ/h
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice