

NAME: LED Wall Pack Light




P/N: WP05-35WAT1A1

Advantage:

- UL cUL DLC certificate
- Lumileds Chip, high CRI
- IP65 driver, input voltage 100-277VAC
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.

Application:

- ◆ entrance lighting, courtyard lighting;
- ◆ Industrial lighting, Outdoor landscape lighting;
- ◆ Building, The hotel;
- ◆ All kinds of residential area.



TECHNICAL DATA SHEET

Product Specifications

Product name	LED Wall Pack Light
Part No	WP05-35WAT1A1
Dimension	204.5*170*123mm

Technical Characteristic

Color temperature	4000K	5000K	5700K
CRI	>70		
Lumen	3850-4200LM		
Lumen Efficacy	110-120LM/W		
Input Power	35W		
Viewing Angle	100*50°		
Input Voltage	100-277VAC	50/60Hz	
Driver model	China Brand Driver		
PF	>0.9		
Waterproof Rating	WET (IP65)		

Materials

LED Brand	LUMILEDS
LED Type	LUXEON 3030 2D (1.5W)
LED QTY	49 PCS
Housing	Aluminum
Optional Accessory	Photocell



Others

Operating Temperature	-20°C TO 45°C
Operating Humidity	20%-90% RH
Storage Temperature	-30°C TO 80°C
Storage Humidity	10%-95%
Application	Outdoor
Safety Certification	UL、cUL、DLC
Warranty Time	5 Years

TECHNICAL DATA SHEET

Light Distribution Testing Parameters

Lumens(lm): 3940.82
 Efficiency(%): 0.00%
 Lumens(lm)/Power(W): 115.23
 Central intensity(cd): 1745.208
 Maximum intensity(cd): 2985.597
 Angle of maximum intensity: C=22.5 γ=29.0
 Beam Angle(50%Imax): [C0/180]Total=101.0
 [C90/270]Total=40.9
 Field angle(10%Imax): [C0/180]Total=125.1
 [C90/270]Total=110.6
 Maximum s/h(1/2): C0_180=1.88 C90_270=1.17
 Maximum s/h(1/4): C0_180=1.70 C90_270=1.00
 Up flux rate of lamp(%): 0.00%
 Down flux rate of lamp(%): 0.00%
 Up flux rate of LUM(%): 0.11%
 Down flux rate of LUM(%): 99.89%
 CIE Type : Direct lighting
 Output flux ratio in π solid angle : 91.811%




Max , Ave Beam angle of C22.5plane107.97

TECHNICAL DATA SHEET

Package

Lamps Net Weight: 1.9Kg/pcs

	Size	Qty/Carton	Weight/Carton
Inner box	236*226*270mm	1 PCS	2.5KG
Outer box	468*249*290mm	2 PCS	5.6KG



Notice For User

- ◆ Please turn off power before install or change assembly parts.
- ◆ The input voltage and lamps should be matched, after connecting the power line, Please make sure the wiring section is insulated.
- ◆ No-professionals, must not install and disassemble the lamps.

Trouble Shootings

Troubles	Check points
Flickering of the light	Turn off the power and turn on again in 3 minutes. If same phenomena occur, then call agencies
Out of working	Please check the connection