

Product Specification Sheet

Product Description	Centaur 22W LED bulkhead 2CCT
Order Code	SLL22CBH/CCT, SLL25CBH/EM/CCT

Technical Specs		
Product Code	SLL22CBH/CCT	SLL25CBH/EM/CCT
Description	Centaur 22W LED bulkhead, 2CCT, 1680lm, white, IP20	Centaur 22W LED bulkhead emergency, 2CCT, 1680lm, white, IP20
Input Voltage	220-240V	220-240V
Total Wattage	22W	24W
Luminaire Lumens	1680lm	1680lm
Lumens P/Watt	76lm/w	70lm/W
LED Chips	2835LED	2835LED
LED Forward Voltage / Current	28.6-35.2V / 700MA	28.6-35.2V / 700MA
LED Chip Lifetime (L70)	60,000 hrs	60,000 hrs
CCT / CRI / SDCM	3000K/4000K / CRI80 / <6	3000K/4000K / CRI80 / <6
Driver	Tridonic 87500735	Tridonic 87500735
Power Factor	0.9	0.9
Running Current	0.12A	0.12A
Inrush Current	8A 80us	8A 80us
Sensor / PIR	N/A	N/A
Emergency Converter	N/A	SL-EM04A-A
Emergency Duration	N/A	3hrs
Emergency Lumens	N/A	150lm
Battery	N/A	NICD 3.6V/2000mAh
Material / Finish (RAL)	Steel base, RAL9010 ABS diffuser, opal	Steel base, RAL9010 ABS diffuser, opal
Class / IP / IK	Class I / IP20 / IK07	Class I / IP20 / IK07
Beam Angle	115°	115°
Glow Wire Testing (TP rating)	650°	650°
Installation Method	Surface mounted	Surface mounted
Temperature	-10~40°C	5~40°C
Warranty	3 years	3 years (battery 2 years)
Certificates	CE	CE

